



Ixxat CAN-IB400/PCI

Item number: 1.01.0293.12001

The Ixxat CAN-IB400/PCI is an active PCI interface card with one CAN channel and galvanic isolation. It is an easy and cost-efficient way to connect computers to a CAN bus network. Based on a modular design, the card enables simple integration into diverse industrial setups, supporting various CAN applications.

PC interface card for CAN (1 x CAN), galv. isolated

Features and benefits

- ✓ **Active CAN interface card**
Fulfills even high requirements in data pre-processing, like precise on-board time-stamping and data filtering.
- ✓ **Cost-effective connectivity**
Offers a cost-effective solution, delivering high performance at an economical price. Ideal choice for demanding applications, without having to compromise on quality.
- ✓ **PCI interface**
PCI (V2.2) plug&play interface supports high-speed data transmission, ideal for demanding industrial applications.
- ✓ **Use in industrial and standard PCs**
PC board with slot plate for fixed installation in desktop or industrial PCs, providing reliable connectivity.
- ✓ **Standard slot bracket**
Standard slot bracket size ensures compatibility with a wide range of PC systems.
- ✓ **Installation of multiple cards**
Integration of multiple cards in one PC allows easy channel extension, making it suitable even for demanding settings like test benches and manufacturing plants.
- ✓ **Modular architecture for easy expansion**
Modern and modular concept enables easy extension with customer specific interfaces via expansion boards and piggyback modules.
- ✓ **Expandable LIN and low-speed CAN channel**
Supports expansion boards for additional low-speed CAN or LIN channel – switchable through software (CAN).
- ✓ **Overvoltage protection**
Galvanic isolation safeguards against overvoltage and protects from potential electrical damage.
- ✓ **Comprehensive driver compatibility**
Ixxat VCI driver packages support multiple fieldbuses and allow easy switching between different PC interface types. Available as free download.
- ✓ **Powerful programming interface**
Ixxat offers versatile programming interfaces for Windows (VCI), Linux (ECI) and real-time OS (on request), enabling flexible development across multiple operating systems.
- ✓ **Analysis software included**
Ixxat canAnalyser3 Mini is included in the VCI V4 download package and enables first steps in analyzing and monitoring CAN networks.



General	
Net Width (mm)	64
Net Height (mm)	120
Net Weight (g)	180
Packed Width (mm)	13
Packed Height (mm)	5
Packed Depth (mm)	17
Packed Weight (g)	185
Operating Temperature °C Min	0
Operating Temperature °C Max	70
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Relative Humidity	10 to 95 %, no condensation
Current Consumption Type Value at Vcc Nom (mA)	100 mA (3.3 VDC), 100 mA (5 V DC)
Input Voltage (V)	3.3/5 V DC via PCI socket
Isolation	1 kV DC for 1 sec.
Content of Delivery	PC interface card, user manual, available as free download: CAN driver VCI, simple CAN monitor "canAnalyser Mini"
Not Included (in delivery)	Comprehensive and powerful driver and software packages are available as free download
Mounting	PCI
Packaging Material	Cardboard



General

Warranty (years) 1

Identification and Status

Product ID 1.01.0293.12001

Country of Origin Germany

HS Code 8517620000

Export Control Classification Number (ECCN) EAR99

Physical Features

Connectors / Input / Output 1 x D-Sub 9 connector, 1 x PCI (V2.2)

CAN Features

CAN Mode CAN high-speed (ISO 11898-2), via optional expansion: CAN low-speed (ISO 11898-3)

CAN Transceiver TLE6250GV33

CAN Controller CAN 2.0 A/B

CAN Baud Rate CAN high-speed: 10 kBit/s to 1 Mbit/s, via optional expansion: CAN low-speed: 10 kBit/s to 125 kBit/s

LIN Features

LIN Mode via optional expansion: LIN (ISO 9141), LIN VBAT 8-48 V DC for product version 3.0 and newer, LIN VBAT 8-18 V DC for product version 2.0 and older

LIN Baud Rate via optional expansion: 10 kBit/s to 25 kBit/s

Certifications and Standards

ETIM Classification EC000515

WEEE Category IT and telecommunications equipment