

Bosch Commercial & VRF systems to BACnet/IP & MS/TP Application

Item number: IN770AIRXXSO000

The Bosch application has been specially designed to allow bidirectional control and monitoring of Bosch Air Flux and Mini-VRF systems from a BMS, SCADA, PLC, or any other device working as a BACnet/IP server or a BACnet MS/TP client. The solution allows the integration of up to 4 indoor units from a single interface.

Bosch to BACnet/IP & MS/TP - Up to 4 Indoor Units

Features and benefits

- ✓ **Compatible with any network**
The interface supports both BACnet/IP and BACnet MS/TP protocols.
- ✓ **Reduce commissioning time**
Scan the bus and find all the units connected to the VRF system with their control signals, including outdoor unit indicators.
- ✓ **A gateway for any project's size**
Choose the license that better fits your needs (XXS - 4 indoor units, S - 16 indoor units, M - 64 indoor units), or upgrade your current license. Your project's dimensions and your budget are covered.
- ✓ **Fast and intuitive project configuration**
Intesis MAPS is the user-friendly, in-house-developed configuration tool that enables you to maximize the potential of Intesis gateways. Simply select your template and eliminate the need for tedious manual signal mapping.
- ✓ **Minimize the use of installation materials, reduce the installation work**
The gateway is connected directly to the outdoor units' communication bus. One single gateway enables centralized access to the entire HVAC system.
- ✓ **Enable energy efficiency by controlling the building's main consuming asset**
The gateway's Power Estimation Algorithm allows you to estimate the energy consumption of each indoor unit present in the VRF system.
- ✓ **Avoid compatibility issues**
This gateway is compatible with Bosch Air Flux and Mini-VRF systems.
- ✓ **Automatic updates will keep your product high performing**
Both the Intesis MAPS configuration tool and the interface's firmware can receive automatic updates to improve the product's functionality.

Bosch Commercial & VRF systems to BACnet/IP & MS/TP Application



General	
Net Weight (g)	240
Packed Width (mm)	106
Packed Height (mm)	58
Packed Depth (mm)	90
Packed Weight (g)	310
Operating Temperature °C Min	0
Operating Temperature °C Max	60
Capacity	Up to 4 indoor units.
Installation Conditions	This gateway is designed to be mounted inside an enclosure. If the unit is mounted outside an enclosure, precautions should always be taken to prevent electrostatic discharge to the unit. When working inside an enclosure (e.g., making adjustments, setting switches, etc.), typical anti-static precautions should always be followed before touching the unit.
AC Model Compatibility	This gateway is compatible with Bosch Air Flux and Mini-VRF systems.
Content of Delivery	Intesis Gateway, Installation Manual, USB Configuration cable.
Not Included (in delivery)	Power supply not included.
Mounting	DIN rail mount (bracket included), Wall mount
Housing Materials	Plastic
Packaging Material	Cardboard
Warranty (years)	3 years

Identification and Status	
Product ID	IN770AIRXXSO000_BAC_BOS
Country of Origin	Spain
HS Code	8517620000

Bosch Commercial & VRF systems to BACnet/IP & MS/TP Application



Identification and Status

Export Control Classification Number (ECCN)	EAR99
--	-------

Physical Features

LED Indicators	Gateway and communication status.
-----------------------	-----------------------------------

Push Buttons	Factory reset. I-Am message (for BACnet only).
---------------------	--

Certifications and Standards


ETIM Classification	EC001604
----------------------------	----------

WEEE Category	IT and telecommunications equipment
----------------------	-------------------------------------


Bosch Commercial & VRF systems to BACnet/IP & MS/TP Application



Use Case



Integration example.



Use Intesis MAPS to change the protocol: BACnet, Modbus, KNX, or Home Automation.