

## Anybus X-gateway - CANopen Slave - PROFINET- IRT FO Device

Item number: AB7943-F

The Anybus X-gateway CANopen Slave to PROFINET-IRT FO Device enables you to connect any CANopen system to any PROFINET-IRT FO control system. Anybus gateways ensure reliable, secure, high-speed data transfers between different industrial networks while being easy to use.



*A protocol converter that connects CANopen and PROFINET-IRT FO control systems*

### Features and benefits

- ✓ **Reach new markets**  
Target new markets using different protocols without needing to change your hardware or software, thereby decreasing your time to market and development costs.
- ✓ **No PLC card slot needed**  
The gateway does not use a card slot in the control system, leaving room for other equipment.
- ✓ **Slim hardware design**  
The gateway is designed for IP20 and DIN-rail mounting, enabling you to install it with ease, close to connected devices, thereby reducing wiring requirements.
- ✓ **3-year warranty**  
The gateway is designed to be robust and long-lasting. A 3-year guarantee is provided
- ✓ **Easy configuration – No programming required!**  
Quickly establish the connection between the two networks with the included Anybus Configuration Manager software. No programming skills are required for the setup process.
- ✓ **Increased PLC performance**  
The gateway allows for fast transfer of cyclic I/O data between the two networks, offloading your PLC from working with additional calculations.
- ✓ **Trusted partner**  
Anybus has a long history of working with all the major network organizations to ensure compliant, high-performing, and compatible products.
- ✓ **Life cycle management**  
HMS maintains every part of the gateway, including network updates, throughout the product's lifecycle.
- ✓

# Anybus X-gateway - CANopen Slave - PROFINET-IRT FO Device



## General

|  |                                    |
|--|------------------------------------|
| Net Width (mm)                                 | 44                                 |
| Net Height (mm)                                | 127                                |
| Net Depth (mm)                                 | 114                                |
| Net Weight (g)                                 | 400                                |
| Packed Width (mm)                              | 17                                 |
| Packed Height (mm)                             | 9                                  |
| Packed Depth (mm)                              | 19                                 |
| Packed Weight (g)                              | 600                                |
| Operating Temperature °C Min                   | -25                                |
| Operating Temperature °C Max                   | 65                                 |
| Storage Temperature °C Min                     | -40                                |
| Storage Temperature °C Max                     | 85                                 |
| Current Consumption Type Value at Vcc Nom (mA) | 200mA @ 24V DC                     |
| Current Consumption Max value at Vcc nom (mA)  | 400mA @ 24V DC                     |
| Input Voltage (V)                              | 24V DC (-20% to +20%)              |
| Power Connector                                | 2-pin, 5.08 Phoenix plug connector |
| Isolation                                      | TRUE                               |
| Mounting                                       | DIN-rail (EN 50022 standard)       |
| Housing Materials                              | Aluminium, Plastic                 |

# Anybus X-gateway - CANopen Slave - PROFINET-IRT FO Device



## General

|                    |           |
|--------------------|-----------|
| Packaging Material | Cardboard |
|--------------------|-----------|

## Identification and Status

|   |            |
|---|------------|
| Product ID                                  | AB7943-F   |
| Country of Origin                           | Sweden     |
| HS Code                                     | 8517620000 |
| Export Control Classification Number (ECCN) | 5A991.b.1  |

## Physical Features

|                             |  |
|-----------------------------|--|
| Connectors / Input / Output | 2x SC-RJ Fiber Optic, 1x D-sub 9-pin male, USB-B Config port |
| DIP & Rotary Switches       | 3x Rotary CAN Address + Baudrate                             |

## CANopen Features

|                                 |                         |
|---------------------------------|-------------------------|
| CANopen Mode                    | Slave mode              |
| CANopen Baud Rate               | 10 kbit/s - 1000 kbit/s |
| CANopen Supported Functionality | PDO, SDO;DS301 v4.02    |
| CANopen Configuration File      | EDS available           |
| CANopen Input Data Size         | 512 bytes               |
| CANopen Output Data Size        | 512 bytes               |

## PROFINET Features

|                                  |   |
|----------------------------------|---|
| PROFINET Mode                    | Slave   |
| PROFINET Supported Functionality | IRT; Acyclic Data exchange; SNMP-MIBII; I&M; LLDP |
| PROFINET Conformance Class       | Class A, Class B, Class C                         |
| PROFINET Configuration File      | GSDML available                                   |
| PROFINET Bandwidth               | 100 Mbit/s fixed                                  |
| PROFINET Input Data Size         | 220 bytes   |

# Anybus X-gateway - CANopen Slave - PROFINET-IRT FO Device



## PROFINET Features

|                           |           |
|---------------------------|-----------|
| PROFINET Output Data Size | 220 bytes |
|---------------------------|-----------|

## Certifications and Standards

|                     |  |
|---------------------|--|
| Protection Class IP | IP20   |
| Recycle / Disposal  | TRUE   |
| UL Information      | E214107: Ord.Loc UL508, CSA C22.2 NO. 142  |
| Environment         | EN 61000-6-4, EN 55016-2-3 Class A, EN 55022 Class A, EN 61000-6-2, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6 |
| WEEE Category       | IT and telecommunications equipment  |



## Use Case

