



## Ewon IIoT Data Starter Kit

Item number: STK205

The Ewon IIoT Data Starter Kit is suitable for both seasoned engineers and Industry 4.0 beginners. It includes the Ewon Flexy 205 gateway, a cost-effective device for remote connectivity and advanced data collection, proven in thousands of successful deployments worldwide.



*Quickly start your IIoT journey*

### Features and benefits

- ✓ **Easily acquire and log data**  
Gather data from PLCs, sensors and other devices thanks to the support of a wide range of industrial protocols, including OPC UA.
- ✓ **Implement efficient data monitoring**  
The Ewon Flexy supports all major PLC protocols for data logging & alarms. Local web-dashboard for KPIs monitoring through Talk2m's M2web service. OPC UA server to share data with Enterprise Systems.
- ✓ **Do more with built-in connectors and APIs**  
You might not have a data application today. But when the time comes, be confident in the fact that you can connect to a local or cloud data solution and make your machine smarter.
- ✓ **Extended data services**  
Wide range of possibilities: PLC data acquisition, alarms, OPC UA, Modbus, MQTT, SNMP, HTTPS, local web-dashboards, cloud live KPIs, and programming (Basic & Java).
- ✓ **Enable machine remote connectivity**  
Enjoy VPN remote access for PLC troubleshooting. The included Talk2m cloud's global infrastructure is redundant and reliable. Setup your device in minutes for unrivalled connectivity success.
- ✓ **Leverage flexible data integration**  
Full flexibility to send data to any server. Multiple IoT connectors, and MQTT/HTTPS through embedded Basic or Java scripting engine. Talk2m Data Services with APIs for third party software integration.
- ✓ **Future-proof thanks to extension cards**  
Discover the interchangeable extension cards of the Ewon Flexy: WiFi, 3G, 4G, USB, Ethernet WAN. These allow you to easily keep up with the evolution of communication technologies.
- ✓ **OPC UA ready**  
Ewon Flexy gateways support OPC UA, a modern protocol for industrial automation. It enables easy machine connectivity, asset modernization, and secure data collection from the factory floor.



General	
Net Width (mm)	55
Net Height (mm)	133
Net Depth (mm)	122
Net Weight (g)	122
Packed Width (mm)	891.5
Packed Height (mm)	320
Packed Depth (mm)	110
Packed Weight (g)	228
Operating Temperature °C Min	-25
Operating Temperature °C Max	+60
Storage Temperature °C Min	-30
Storage Temperature °C Max	+70
Relative Humidity	10 to 95% relative humidity (non-condensing).
Input Voltage (V)	12-24VDC+/-20% , LPS。消费：取决于安装的扩展卡（请参阅我们网站上的安装指南）。
Power Connector	9-pole
Configuration	Web-Based configuration: Embedded web interface with setup wizards for configuration and maintenance (no extra software needed). Authentication with login/password and user management capability. Possibility of uploading custom web GUI.
Content of Delivery	This product consists of the following components: an Ewon FLEXY205 gateway, a WIFI extension board, an IO extension board, an IO demo board, one power supply set (consisting of a power supply, 3 plugs (for EU, UK & US markets), 2 power connectors and a cardboard box), a grey Ethernet cable of 1m length, a branded screw driver, a welcome leaflet and a branded cardboard box.
Not Included (in delivery)	1pc per customer only
Mounting	DIN rail mount (bracket included), Wall mount



## General

<b>Housing Materials</b>	Plastic
<b>Packaging Material</b>	Cardboard
<b>Warranty (years)</b>	3

## Identification and Status

<b>Product ID</b>	STK205
<b>Model Code</b>	02801
<b>Country of Origin</b>	Belgium
<b>HS Code</b>	8517699000
<b>Export Control Classification Number (ECCN)</b>	EAR99

## Physical Features

<b>Connectors / Input / Output</b>	4 x RJ45 Ethernet port: 10/100 Mb. Configurable LAN/WAN ports, port 1 always LAN, 2x Digital input: 0 to 12/24VDC; 1.5kV isolation, 1x Digital output: open drain (MOSFET) 200mA; 1.5 kV isolation.
------------------------------------	---

## Certifications and Standards

<b>Environment</b>	Temperature - Operating & Storage tested according to: IEC 60068-2-1 Cold test, IEC 60068-2-2 Dry heat test, IEC 60068-2-14 Change of temperature, IEC 60068-2-30 Cyclic damp heat test
<b>Vibration and Shock</b>	Vibration & shocks tested according to: IEC 60068-2-27 Bumps, IEC 60068-2-64 Vibration (broad-band random), IEC 60068-2-6 Vibration (sinusoidal)
<b>WEEE Category</b>	IT and telecommunications equipment
<b>Other Certification</b>	Giteki Japan, Russia FSS notification