

Mitsubishi Electric Domestic, Mr.Slim and City Multi to KNX Interface

Item number: INKNXMIT001I000

The Mitsubishi Electric-KNX interface allows full bidirectional communication between Mitsubishi Electric domestic, Mr. Slim, and City Multi air conditioner units and KNX installations. It connects directly to the indoor unit and delivers complete interoperability with KNX.



Mitsubishi Electric Domestic to KNX - 1 indoor unit

Features and benefits

- ETS configuration
 The interface is configured using the ETS standard configuration tool software.
- Multiple energy efficiency functions available Timeout, open window, or occupancy energy-saving functions are available to reduce energy costs.
- Total unit control and monitoring from KNX

 Through internal variables, running hours counter (for maintenance purposes), and error indication.
- AC unit control by both remote controller and KNX

 The AC unit can be simultaneously controlled by the manufacturer's remote controller and KNX.

- Compatible with all KNX thermostats in the market
 All the required DPT objects to be compatible with all KNX thermostats in the market are available.
- Smooth KNX thermostat integration
 KNX thermostats are allowed to control the AC unit via the thermostat's temperature sensor.
- Up to five scenes saved/executed from KNX
 Up to five scenes can be saved and executed from KNX.
- Compact dimensions, allowing inside installation

 The interface can be quickly installed inside the AC unit thanks to its reduced dimensions.



Mitsubishi Electric Domestic, Mr.Slim and City Multi to KNX Interface




General	
Net Width (mm)	36
Net Height (mm)	21
Net Depth (mm)	59
Net Weight (g)	110
Capacity	1 indoor unit.
Installation Conditions	This gateway is designed to be mounted inside an enclosure. If the unit is mounted outside an enclosure, precautions should always be taken to prevent electrostatic discharge to the unit. When working inside an enclosure (e.g., making adjustments, setting switches, etc.), typical anti-static precautions should always be followed before touching the unit.
Content of Delivery	Intesis Gateway, Installation Manual, AC Connection cable.
Warranty (years)	3 years
Identification and Status	
Product ID	INKNXMIT001I000
Country of Origin	Spain
HS Code	8517620000
Export Control Classification Number (ECCN)	EAR99
Certifications and Standards	
ETIM Classification	EC001604
WEEE Category	IT and telecommunications equipment



Mitsubishi Electric Domestic, Mr.Slim and City Multi to KNX Interface



Use Case



Integration example.

