

Anybus CompactCom 40 Brick Modbus Serial Interface - CC-Link IE Field

Item number: AB6795-D

The Anybus CompactCom 40 Brick Modbus Serial Interface is a communication interface that can be embedded into any serial device or machine to enable communication to CC-Link IE Field networks. The pluggable design enables integration late in the assembly process, the addition of specific network connectors, and compliance with protection class requirements.



Enable communication between industrial devices and CC-Link IE Field networks

Features and benefits

- ✓ **High performance**
Powered by the award-winning NP40 network processor, the Anybus CompactCom guarantees fast data transfer and low latency, making it ideal for the most demanding industrial applications.
- ✓ **Quick time to market**
HMS provides comprehensive support throughout the integration journey, ensuring a quick time to market.
- ✓ **Life cycle management**
HMS maintains every part of the Anybus CompactCom, including network updates, throughout the product's lifecycle.
- ✓ **Fully embedded – meet IP requirements**
The brick can be fully embedded within your product, conserving valuable space, and enabling you to provide IP class-certified protection.
- ✓ **Simplified integration**
The Anybus CompactCom Modbus Serial is an easy-to-use, low-cost communication solution tailored for simple industrial field devices.
- ✓ **Versatile Event-Based Hardware Interfaces**
Enjoy fast and flexible event-based application hardware interfaces with the option to choose from 8/16-bit parallel or high-speed SPI, and I/O via the shift register interface.
- ✓ **CLPA pre-certified**
Pre-certified for CLPA network compliance, enabling faster network certification.
- ✓ **Design flexibility**
Add your own connectors and peripherals, offering design flexibility that matches your unique needs.
- ✓ **Robust Security Measures**
Mandatory software signatures prevent unauthorized downloads to the Anybus CompactCom, while robust encryption techniques safeguard against illicit copying.
- ✓ **Supports hardware changes**
Possible to swap or install late in the manufacturing process.

Anybus CompactCom 40 Brick Modbus Serial Interface - CC-Link IE Field



General	
Net Weight (g)	34
Packed Width (mm)	12
Packed Height (mm)	2
Packed Depth (mm)	8
Packed Weight (g)	50
Operating Temperature °C Min	-40
Operating Temperature °C Max	70
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Class (CompactCom series)	C
Input Voltage (V)	3.3 VDC, +/- 0.15 VDC
Application Interface	8/16-bit parallel (30 ns access) High speed SPI, baudrate configurable up to 20 MHz I/O (shift register interface, cyclical update time 82 µs) UART (for backwards compatibility with 30-series, max 625kbps)
Isolation	Galvanic Isolation
Content of Delivery	CompactCom B40 module
Mounting	PCB mounting via a customized CompactFlash connector
Warranty (years)	1 year
Identification and Status	
Product ID	AB6795-D
Country of Origin	Sweden
HS Code	8517620000

Anybus CompactCom 40 Brick Modbus Serial Interface - CC-Link IE Field



Identification and Status

Export Control Classification Number (ECCN)	3A991.a.2
---	-----------

Physical Features

Form Factor	Brick (pluggable)
-------------	-------------------