

Panasonic ECOi, PACi, ECOg / PAC, VRF systems to Modbus TCP/RTU Application

Item number: IN770AIR00SO000

The Panasonic application has been specially designed to allow bidirectional control and monitoring of Panasonic ECOi, PACi, ECOg / PAC, VRF systems from a BMS, SCADA, PLC, or any other device working as a Modbus client. The solution allows the integration of up to 16 indoor units from a single interface.



Panasonic to Modbus TCP/RTU - Up to 16 Indoor Units

Features and benefits

- Simultaneous Modbus TCP and RTU management

 The gateway is a Modbus server and is able to manage both

 Modbus TCP and Modbus RTU simultaneously.
- Automatic identification
 A scan function is available for automatic identification of the units present in the VRF system.
- Individual indoor unit energy consumption signals

 Energy consumption signals from each indoor unit are available, so they can be checked individually.
- Commissioning-friendly approach with Intesis MAPS

 Templates can be imported and reused as often as needed, significantly reducing commissioning time.

- Direct access to the outdoor unit Connection is simple, as the interface connects directly to the outdoor unit's communication bus.
- Outdoor unit signals
 Signals assigned to the outdoor unit are available to be used in the integration.
- Multiple TCP client support

 The interface supports up to 6 TCP clients (incoming sockets)
- Configuration tool and interface automatic updates
 Both the Intesis MAPS configuration tool and the interface's firmware can receive automatic updates.



Panasonic ECOi, PACi, ECOg / PAC, VRF systems to Modbus TCP/RTU Application



General	
Net Width (mm)	106
Net Height (mm)	58
Net Depth (mm)	90
Net Weight (g)	240
Packed Width (mm)	13
Packed Height (mm)	8.5
Packed Depth (mm)	14
Packed Weight (g)	310
Operating Temperature °C Min	0
Operating Temperature °C Max	60
Input Voltage (V)	For DC: 12 36 VDC \pm 10%, Max: 250 mA For AC: 24 VAC \pm 10 %, 50-60 Hz, Max: 127 mA Recommended voltage: 24 VDC, Max: 127 mA
Power Connector	3-pole
Capacity	Up to 16 indoor units and up to 16 outdoor units.
Installation Conditions	This gateway is designed to be mounted inside an enclosure. If the unit is mounted outside an enclosure, precautions should always be taken to prevent electrostatic discharge to the unit. When working inside an enclosure (e.g., making adjustments, setting switches, etc.), typical anti-static precautions should always be followed before touching the unit.
Content of Delivery	Intesis Gateway, Installation Manual, USB Configuration cable.
Not Included (in delivery)	Power supply not included.
Mounting	DIN rail mount (bracket included), Wall mount
Housing Materials	Plastic
Warranty (years)	3 years



Panasonic ECOi, PACi, ECOg / PAC, VRF systems to Modbus TCP/RTU Application



General

Packaging Material Cardboard

Identification and Status

Product ID	IN770AIR00SO000_MBS_PAN
Country of Origin	Spain
HS Code	8517620000
Export Control Classification Number (ECCN)	EAR99

Physical Features

Connectors / Input / Output	Power supply, EIA-485, KNX, Ethernet, HVAC port, Binary inputs (dry contact), Console port USB.
LED Indicators	Gateway and communication status.
Push Buttons	Factory reset. I-Am message (for BACnet only). Normal mode/programming mode switch (for KNX only).
DIP & Rotary Switches	EIA-485 serial port configuration.

Certifications and Standards

ETIM Classification	EC001604
WEEE Category	IT and telecommunications equipment



Panasonic ECOi, PACi, ECOg / PAC, VRF systems to Modbus TCP/RTU Application



Use Case

Panasonic Modbus RTU Modbus TCP Interis LISTE P-Link HMI

Integration example.



Use Intesis MAPS to change the protocol: BACnet, Modbus, KNX, or Home Automation $\,$

