



Hisense VRF systems to BACnet/IP & MS/TP

Item number: INBACHIS0160000

This Hisense application was designed to allow bidirectional control and monitoring of Hisense VRF systems from a BMS, SCADA, PLC, or any other device working as a BACnet/IP server or a BACnet MS/TP client. The solution allowed the integration of up to 16 indoor units from a single interface. Please refer to the new product reference for further details.



Replaced by: IN770AIR00S0000

Features and benefits



General

| | |
|--------------------|---------|
| Net Width (mm) | 88 |
| Net Height (mm) | 56 |
| Net Depth (mm) | 90 |
| Net Weight (g) | 270 |
| Packed Width (mm) | 13 |
| Packed Height (mm) | 9 |
| Packed Depth (mm) | 13 |
| Packed Weight (g) | 380 |
| Warranty (years) | 3 years |

Identification and Status

| | |
|---|-------------------------|
| Product ID | INBACHIS016O000 |
| Successor | IN770AIR00SO000_BAC_HIS |
| Country of Origin | Spain |
| HS Code | 8517620000 |
| Export Control Classification Number (ECCN) | EAR99 |

Certifications and Standards

| | |
|---------------------|----------|
| ETIM Classification | EC001604 |
|---------------------|----------|



Use Case

Hisense

