

M-Bus to Modbus-TCP gateway

Item number: 024380-C

The Anybus M-Bus to Modbus TCP gateway decodes M-Bus telegrams for easy overview and mapping of meter values. You can connect several M-Bus slaves to the gateway (two versions are available — for 20 or 80 loads) and enable them to communicate on a Modbus-TCP network.



Make M-Bus measuring devices talk Modbus-TCP

Features and benefits



M-Bus to Modbus-TCP gateway

General

| | |
|---|------------------------------|
| Net Weight (g) | 50 |
| Packed Width (mm) | 14 |
| Packed Height (mm) | 5 |
| Packed Depth (mm) | 17 |
| Packed Weight (g) | 140 |
| Operating Temperature °C Min | 0 |
| Operating Temperature °C Max | 50 |
| Current Consumption Type Value at Vcc Nom (mA) | 300mA @ 24V DC |
| Mounting | DIN-rail (EN 50022 standard) |
| Housing Materials | Plastic |

Identification and Status

| | |
|--|------------|
| Product ID | 024380-C |
| Country of Origin | Germany |
| HS Code | 8517620000 |
| Export Control Classification Number (ECCN) | EAR99 |

Certifications and Standards

| | |
|---------------------|------|
| Protection Class IP | IP20 |
|---------------------|------|