

## Anybus X-gateway - DeviceNet Adapter - PROFINET-IRT Device

Item number: AB7509-F

The Anybus X-gateway DeviceNet Adapter to PROFINET-IRT Device enables you to connect any DeviceNet system to any PROFINET-IRT control system. Anybus gateways ensure reliable, secure, high-speed data transfers between different industrial networks while being easy to use.



*A protocol converter that connects DeviceNet and PROFINET-IRT control systems*

### Features and benefits

- ✓ **Reach new markets**  
Target new markets using different protocols without needing to change your hardware or software, thereby decreasing your time to market and development costs.
- ✓ **Slim hardware design**  
The gateway is designed for IP20 and DIN-rail mounting, enabling you to install it with ease, close to connected devices, thereby reducing wiring requirements.
- ✓ **Easy configuration – No programming required!**  
Quickly establish the connection between the two networks with the included Anybus Configuration Manager software. No programming skills are required for the setup process.
- ✓ **Trusted partner**  
Anybus has a long history of working with all the major network organizations to ensure compliant, high-performing, and compatible products.
- ✓ **No PLC card slot needed**  
The gateway does not use a card slot in the control system, leaving room for other equipment.
- ✓ **3-year warranty**  
The gateway is designed to be robust and long-lasting. A 3-year guarantee is provided.
- ✓ **Increased PLC performance**  
The gateway allows for fast transfer of cyclic I/O data between the two networks, offloading your PLC from working with additional calculations.
- ✓ **Life cycle management**  
HMS maintains every part of the gateway, including network updates, throughout the product's lifecycle.

# Anybus X-gateway - DeviceNet Adapter - PROFINET-IRT Device



General	
Net Width (mm)	44
Net Height (mm)	127
Net Depth (mm)	114
Net Weight (g)	400
Packed Width (mm)	17
Packed Height (mm)	9
Packed Depth (mm)	19
Packed Weight (g)	600
Operating Temperature °C Min	-25
Operating Temperature °C Max	65
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Type Value at Vcc Nom (mA)	200mA @ 24V DC
Current Consumption Max value at Vcc nom (mA)	400mA @ 24V DC
Input Voltage (V)	24V DC (-20% to +20%)
Power Connector	2-pin, 5.08 Phoenix plug connector
Isolation	TRUE
Mounting	DIN-rail (EN 50022 standard)
Housing Materials	Aluminium, Plastic

# Anybus X-gateway - DeviceNet Adapter - PROFINET-IRT Device



## General

Packaging Material	Cardboard
--------------------	-----------

## Identification and Status

Product ID	AB7509-F
Country of Origin	Sweden
HS Code	8517620000
Export Control Classification Number (ECCN)	5A991.b.1

## Physical Features

Connectors / Input / Output	2x RJ45, 1x 5-pin, 5.08 Phoenix plug connector, USB-B Config port
DIP & Rotary Switches	1x 8-dip switch DEV MacID + Baud rate

## DeviceNet Features

DeviceNet Mode	Adapter / Slave
DeviceNet Configuration File	EDS available
DeviceNet Baud Rate	125-500 kbit/s
DeviceNet Input Data Size	512 bytes
DeviceNet Output Data Size	512 bytes

## PROFINET Features

PROFINET Mode	Slave
PROFINET Supported Functionality	IRT, SNMP
PROFINET Configuration File	GSDML available
PROFINET Bandwidth	100MBit full duplex down to 1ms cycle time
PROFINET Input Data Size	512 bytes
PROFINET Output Data Size	512 bytes

## Certifications and Standards

Protection Class IP	IP20
---------------------	------

# Anybus X-gateway - DeviceNet Adapter - PROFINET-IRT Device



Certifications and Standards	
Recycle / Disposal	TRUE
UL Information	E214107: Ord.Loc UL508, CSA C22.2 NO. 142
Environment	EN 61000-6-4, EN 55016-2-3 Class A, EN 55022 Class A, EN 61000-6-2, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6
WEEE Category	IT and telecommunications equipment