

Anybus X-gateway – DeviceNet Scanner - CC-Link IE Field Slave

Item number: AB7955-F

The Anybus X-gateway DeviceNet Master to CC-Link IE Field Slave enables you to connect any DeviceNet device or equipment to CC-Link IE Field control systems. It can be used when there is no existing DeviceNet control system. Anybus gateways ensure reliable, secure, high-speed data transfers between different industrial networks while being easy to use.



A protocol converter that connects DeviceNet devices to CC-Link IE Field PLCs

Features and benefits

✓ Reach new markets

Target new markets using different protocols without needing to change your hardware or software, thereby decreasing your time to market and development costs.

✓ Slim hardware design

The gateway is designed for IP20 and DIN-rail mounting, enabling you to install it with ease, close to connected devices, thereby reducing wiring requirements.

✓ Easy configuration – No programming required!

Quickly establish the connection between the two networks with the included Anybus Configuration Manager software. No programming skills are required for the setup process.

✓ Trusted partner

Anybus has a long history of working with all the major network organizations to ensure compliant, high-performing, and compatible products.



✓ No PLC card slot needed

The gateway does not use a card slot in the control system, leaving room for other equipment.

✓ 3-year warranty

The gateway is designed to be robust and long-lasting. A 3-year guarantee is provided.

✓ Increased PLC performance

The gateway allows for fast transfer of cyclic I/O data between the two networks, offloading your PLC from working with additional calculations.

✓ Life cycle management

HMS maintains every part of the gateway, including network updates, throughout the product's lifecycle.

Anybus X-gateway – DeviceNet Scanner - CC-Link IE Field Slave



General

Net Width (mm)	44
Net Height (mm)	127
Net Depth (mm)	114
Net Weight (g)	400
Packed Width (mm)	17
Packed Height (mm)	9
Packed Depth (mm)	19
Packed Weight (g)	750
Operating Temperature °C Min	-25
Operating Temperature °C Max	65
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Type Value at Vcc Nom (mA)	200mA @ 24V DC
Current Consumption Max value at Vcc nom (mA)	400mA @ 24V DC
Input Voltage (V)	24V DC (-20% to +20%)
Power Connector	2-pin, 5.08 Phoenix plug connector
Isolation	TRUE
Mounting	DIN-rail (EN 50022 standard)
Housing Materials	Aluminium, Plastic

Anybus X-gateway – DeviceNet Scanner - CC-Link IE Field Slave



General

Packaging Material	Cardboard
--------------------	-----------

Identification and Status

Product ID	AB7955-F
Country of Origin	Sweden
HS Code	8517620000
Export Control Classification Number (ECCN)	5A991.b.4b

Physical Features

Connectors / Input / Output	1x 5-pin, 5.08 Phoenix plug connector, 2x RJ45, USB-B Config port
DIP & Rotary Switches	1x 8-dip switch DEV MacID + Baud rate, 1x 8-dip switches for Station Number

CC-Link IE Field Features

CC-Link IE Field Mode	Slave
CC-Link IE Field Supported Functionality	CC-Link IE Field Network Intelligent Device Station
CC-Link IE Field Bandwidth	1 Gbit/s fixed
CC-Link IE Field Input Data Size	512 bytes
CC-Link IE Field Output Data Size	512 bytes

DeviceNet Features

DeviceNet Mode	Scanner / Master
DeviceNet Supported Functionality	Communications Adapter profile 12; Bit strobe; Polling; Cyclic; COS; LiveList
DeviceNet No. Of Adapters	63
DeviceNet Baud Rate	125-500 kbit/s
DeviceNet Input Data Size	512 bytes
DeviceNet Output Data Size	512 bytes

Certifications and Standards

Protection Class IP	IP20
---------------------	------

Anybus X-gateway – DeviceNet Scanner - CC-Link IE Field Slave



Certifications and Standards	
Recycle / Disposal	TRUE
UL Information	E214107: Ord.Loc UL508, CSA C22.2 NO. 142
Environment	EN 61000-6-4, EN 55016-2-3 Class A, EN 55022 Class A, EN 61000-6-2, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6
WEEE Category	IT and telecommunications equipment