

Ixxat CAN cable

Item number: 1.04.0076.00180

The Ixxat CAN cable (2.0 m length) with D-Sub 9 male to female connectors ensures reliable connectivity for components in CAN and CAN FD systems. Its shielded design and twisted wires ensure minimal interference and reliable data transmission.



Connects CAN/CAN FD components (D-Sub 9 socket to plug)

Features and benefits

✓ **Robust connectivity**

Features a 9-pin D-Sub plug to socket design, enabling flexible connections to various devices.

✓ **Simplified installation**

Features a direct 1-to-1 pin assignment, making connection straightforward.

✓ **Easy network integration**

Allows easy integration into CAN or CAN FD networks with a length of 200 cm (cable length without connectors: 190 cm).

✓ **Technical data overview**

Contact resistance: 10 mOhm / testing voltage: 800 V / rated voltage: 350 V / temperature range: 0 °C to 70 °C



General

| | |
|--------------------|-----|
| Net Weight (g) | 110 |
| Packed Width (mm) | 12 |
| Packed Height (mm) | 2 |
| Packed Depth (mm) | 11 |
| Packed Weight (g) | 110 |

Identification and Status

| | |
|---|-----------------|
| Product ID | 1.04.0076.00180 |
| Successor | XXX |
| Country of Origin | China |
| HS Code | 8544429090 |
| Dual Usage | No |
| Export Control Classification Number (ECCN) | EAR99 |

Physical Features

| | |
|------------------|----|
| Contains Battery | No |
|------------------|----|

Certifications and Standards

| | |
|---------------------|-------------------------------------|
| ETIM Classification | EC002584 |
| WEEE Category | IT and telecommunications equipment |