



Ixxat CAN-IB120/PCIe Mini

Item number: 1.01.0237.21000

The Ixxat CAN-IB120/PCIe Mini is a passive PCI Express Mini interface card with two CAN channels and a back-entry CAN socket. It is an easy and cost-efficient way to connect computers to a CAN bus network. Thanks to its very compact dimensions, the card is especially suitable for applications with limited space.

PC interface card for CAN (2 x CAN)

Features and benefits

- ✓ **Passive CAN interface card**
Direct access to CAN networks – suitable for applications where a straightforward, microcontroller-free connection is required.
- ✓ **PCle Mini interface**
Single-lane (1x) PCI Express interface supports high-speed data transmission, ideal for demanding industrial applications.
- ✓ **Back entry CAN socket**
CAN socket is aligned at the card's end, perfect for systems that require easy rear access for connectivity.
- ✓ **Comprehensive driver compatibility**
Ixxat VCI driver packages support multiple fieldbuses and allow easy switching between different PC interface types. Available as free download.
- ✓ **Analysis software included**
Ixxat canAnalyser3 Mini is included in the VCI V4 download package and enables first steps in analyzing and monitoring CAN networks.
- ✓ **Cost-effective connectivity**
Offers a cost-effective solution, delivering high performance at an economical price. Ideal choice for demanding applications, without having to compromise on quality.
- ✓ **Compact PCIe Mini form factor**
With its PCIe Mini form factor, this variant is ideal for small devices and mobile applications with limited available space.
- ✓ **Installation of multiple cards**
Integration of multiple cards in one PC allows easy channel extension, making it suitable even for demanding settings like test benches and manufacturing plants.
- ✓ **Powerful programming interface**
Ixxat offers versatile programming interfaces for Windows (VCI), Linux (ECI) and real-time OS (on request), enabling flexible development across multiple operating systems.



General	
Net Width (mm)	30
Net Height (mm)	51
Net Weight (g)	130
Packed Width (mm)	13
Packed Height (mm)	17
Packed Depth (mm)	4
Packed Weight (g)	130
Operating Temperature °C Min	-40
Operating Temperature °C Max	85
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Relative Humidity	10 to 95 %, non-condensing
Current Consumption Max value at Vcc nom (mA)	230 mA (3.3 V DC)
Input Voltage (V)	3.3 V DC via PCIe Mini socket
Content of Delivery	PC interface card, user manual, CAN connection cable open style (20 cm, 03SUR-32S to SM03B-SURS-TF), available as free download: CAN driver VCI, simple CAN monitor "canAnalyser Mini"
Not Included (in delivery)	Comprehensive and powerful driver and software packages are available as free download
Mounting	Mini PCI Express
Packaging Material	Cardboard
Warranty (years)	1



Identification and Status

Product ID	1.01.0237.21000
Country of Origin	Germany
HS Code	8517620000
Dual Usage	No
Export Control Classification Number (ECCN)	EAR99

Physical Features

Connectors / Input / Output	2 x CAN connector type SM03B-SURS-TF by JST, 1 x PCI Express Mini Base Specification (V1.1), single lane port (x1)
Contains Battery	No

CAN Features

CAN Mode	CAN high-speed (ISO 11898-2)
CAN Transceiver	TI SN65HVD230
CAN Controller	CAN 2.0 A/B
CAN Baud Rate	10 kBit/s to 1 Mbit/s

Certifications and Standards

ETIM Classification	EC000515
CE	Yes
FCC	Yes
TELEC	No
WEEE Category	IT and telecommunications equipment