

Ixxat D-Sub 9 connector with two CAN terminations

Item number: 1.04.0075.30003

The Ixxat Sub-D9 connector with two CAN terminations ensures proper termination of CAN and CAN FD buses. It features a D-Sub 9 male to female gender changer design and is used when a CAN node lacks internal termination or if no CAN node is connected at the end of the CAN bus. Per ISO 11898-2, high-speed CAN systems require end resistors.



Termination for CAN/CAN FD networks (D-Sub 9 plug)

Features and benefits

✓ **Optimal signal integrity with two terminations**

Integrates two 120 Ohm resistors, ensuring proper CAN/CAN FD bus termination. The resistors are placed between pin 2 (CAN-L) and pin 7 (CAN-H), as well as between pin 1 and 4.

✓ **Technical data overview**

Insulator: PBT glass fiber reinforced / contact: brass, gold plated over nickel / shell: tin plated / insulator resistance: 500 MOhm min. at 500 V DC / temperature range: -55 °C to 105 °C

Ixxat D-Sub 9 connector with two CAN terminations



General	
Net Weight (g)	12
Packed Weight (g)	12
Identification and Status	
Product ID	1.04.0075.30003
Country of Origin	China
HS Code	8536901000
Dual Usage	No
Export Control Classification Number (ECCN)	EAR99
Physical Features	
Contains Battery	No
Certifications and Standards	
ETIM Classification	EC002584
WEEE Category	IT and telecommunications equipment