

Anybus Communicator – PROFINET IO Device to Modbus-TCP server

Item number: ABC4017-A

The Anybus Communicator PROFINET IO Device to Modbus-TCP server enables you to connect any PROFINET IO control system to any Modbus-TCP control system. Anybus Communicators ensure reliable, secure, high-speed data transfers between different industrial networks. Thanks to our intuitive web-based user interface, they're also incredibly easy to use.



A protocol converter that connects PROFINET IO and Modbus-TCP control systems

Features and benefits

- ✓ **Intuitive user interface**
Use the intuitive web-based user interface to easily configure the Communicator via the drag-and-drop functionality or to analyze live data, export log files, and generate support packages.
- ✓ **High performance**
Powered by the award-winning NP40 network processor and high-end components, the Communicator meets the constantly growing demand for more data to be transferred faster.
- ✓ **Instant data transfer**
Instant data transfer lets you take advantage of high-speed industrial networks, as the Communicator provides hardware-accelerated endian conversion (byte swap), saving processing time on the PLC.
- ✓ **Ensures uptime**
Thanks to carefully selected industrial components the Communicator operates reliably in harsh industrial environments ensuring uptime and a long life.
- ✓ **Brand Labeling**
Pre-configure the Communicator and customize the hardware and user interface with your colors and logos.
- ✓ **Cybersecurity**
The secure boot protects against malware, while a security switch locks configurations to prevent unauthorized changes. Ports used in production are disabled to add another layer of security.
- ✓ **Optimized hardware design**
The Communicator has forward-facing ports and is designed for IP20 and DIN-rail mounting, enabling you to install it with ease, close to connected devices, thereby reducing wiring requirements.
- ✓ **5-year warranty**
The Communicator is made to be durable and have a long life. We're so confident in its quality that we provide a 5-year warranty.
- ✓ **Instant diagnostics**
The user interface displays real-time connection status and I/O data mapping for easy troubleshooting. Easily generate a support file containing all the necessary information.
- ✓ **Life cycle management**
HMS maintains every part of the Communicator, including network updates, throughout the product's lifecycle.

Anybus Communicator – PROFINET IO Device to Modbus-TCP server



General

Net Width (mm)	27
Net Height (mm)	144
Net Depth (mm)	98
Net Weight (g)	150
Packed Width (mm)	35
Packed Height (mm)	170
Packed Depth (mm)	115
Packed Weight (g)	185
Operating Temperature °C Min	-25
Operating Temperature °C Max	70
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Type Value at Vcc Nom (mA)	90mA @ 24V DC (2.2W)
Current Consumption Max value at Vcc nom (mA)	125mA @24V DC (3W)
Input Voltage (V)	12-30V DC
Power Connector	3-pin, 5.08 Phoenix plug connector
Reverse Polarity Protection	Yes
Short Circuit Protection	Yes
Isolation	TRUE

Anybus Communicator – PROFINET IO Device to Modbus-TCP server



General

Mounting	DIN-rail (EN 50022 standard)
Housing Materials	PC ABS, UL 94 VO
Packaging Material	Cardboard
Warranty (years)	5

Identification and Status

Product ID	ABC4017-A
Model Code	40-ETH-ETH-B
Predecessor	AB7650-F
Country of Origin	Sweden
HS Code	8517620000
Dual Usage	No
Export Control Classification Number (ECCN)	5A991.b.1

Physical Features

Connectors / Input / Output	2x RJ45, 2xRJ45, RJ45 Config port
Push Buttons	Factory reset
Contains Battery	No

Modbus-TCP Features

Modbus-TCP Mode	Slave / Server
Modbus-TCP Supported Functionality	Modbus specification V1.1b3; 4 connections; Daisy chaining
Modbus-TCP Functions Supported	1, 2, 3, 4, 5, 6, 15, 16, 23, 43/14
Modbus-TCP Bandwidth	10/100 Mbit/s
Modbus-TCP Input Data Size	1500 bytes

Anybus Communicator – PROFINET IO Device to Modbus-TCP server



Modbus-TCP Features

Modbus-TCP Output Data Size	1500 bytes
-----------------------------	------------

PROFINET Features

PROFINET Mode	Slave
---------------	-------

PROFINET Supported Functionality	RT; Daisy chaining;
----------------------------------	---------------------

PROFINET Conformance Class	Class B
----------------------------	---------

PROFINET Configuration File	GSDML available
-----------------------------	-----------------

PROFINET Bandwidth	10/100MBit down to 1ms cycle time
--------------------	-----------------------------------

PROFINET Input Data Size	1024 bytes
--------------------------	------------

PROFINET Output Data Size	1024 bytes
---------------------------	------------

Certifications and Standards

Protection Class IP	IP20
---------------------	------

ETIM Classification	EC001604
---------------------	----------

CE	Yes
----	-----

UL	Yes
----	-----

UL Information	E214107: Ord.Loc UL 61010-1, CSA C22.2 No. 61010-1, UL 61010-2-201, CSA C22.2 No. 61010-2-201
----------------	---

ATEX	No
------	----

KC	Yes
----	-----

EMC	Yes
-----	-----

Environment	EN 55016-2-3 Class A, EN 55032 Class A, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6
-------------	--

Waste Certification (WEEE)	Yes
----------------------------	-----

WEEE Category	IT and telecommunications equipment
---------------	-------------------------------------



Use Case



The communicator can be used wherever there is a need to transfer data between control systems using different industrial protocols.