

Universal IR Air Conditioner to BACnet MS/TP or Modbus RTU

Item number: IN485UNI001I100

This universal gateway allows the integration of any air conditioning unit provided with an infrared receiver into a BACnet MS/TP or a Modbus RTU network. The gateway communicates via infrared with the indoor unit and provides bidirectionality due to its embedded IR receiver.



IR air conditioning to BACnet MS/TP or Modbus RTU - 1 indoor unit

Features and benefits

Universal IR Air Conditioner to BACnet MS/TP or Modbus RTU



General	
Net Width (mm)	53
Net Height (mm)	58
Net Depth (mm)	93
Net Weight (g)	52
Packed Width (mm)	151
Packed Height (mm)	98
Packed Depth (mm)	85
Packed Weight (g)	361
Capacity	1 indoor unit.
Installation Conditions	This gateway is designed to be mounted inside an enclosure. If the unit is mounted outside an enclosure, precautions should always be taken to prevent electrostatic discharge to the unit. When working inside an enclosure (e.g., making adjustments, setting switches, etc.), typical anti-static precautions should always be followed before touching the unit.
Warranty (years)	3 years

Identification and Status	
Product ID	IN485UNI001I100
Country of Origin	Spain
HS Code	8517620000
Dual Usage	No
Export Control Classification Number (ECCN)	EAR99

Physical Features	
Contains Battery	No

Certifications and Standards	
ETIM Classification	EC001604