

Anybus PoE injector 12-57VDC

Item number: AWB4006-B

The Anybus Power over Ethernet Injector (PoE) makes it possible to supply an Anybus product, for example an Anybus WLAN Access point or Anybus Wireless Bolt RJ45, with power through an Ethernet cable.

onturno	and	benefits
Edlui ES	anu	NELIELITS

Supports PoE

Removes the need for an additional power cable.



Flexible mounting

DIN-Rail and Wall Mount Design



Power your Anybus device through a single Ethernet cable



2-port Gigabit High Power injector with a rigid IP30 metal enclosure.



Anybus PoE injector 12-57VDC

1	2
1	li

General	
Net Weight (g)	500
Packed Width (mm)	15
Packed Height (mm)	5
Packed Depth (mm)	20
Packed Weight (g)	515
Operating Temperature °C Min	-20°C
Operating Temperature °C Max	70°C
Storage Temperature °C Min	-40°C
Storage Temperature °C Max	80°C
Input Voltage (V)	12-57 VDC
Output Voltage	50 VDC
Power Connector	Other
Short Circuit Protection	Yes
Housing Materials	Metal Housing
Packaging Material	Cardboard
Warranty (years)	3 years
Identification and Status	

Identification and Status

Product ID	AWB4006-B
Country of Origin	Taiwan (Province of China)
HS Code	8517620000



Anybus PoE injector 12-57VDC

Identification and Status



Physical Features

Export Control Classification

Contains Battery

Number (ECCN)

Dual Usage

No

No

5A992.c

Certifications and Standards		
Protection Class IP	IP30	
CE	Yes	

