

DALI to BACnet IP & MS/TP Server gateway

Item number: INBACDAL0640200

Designed for the integration of any DALI/DALI-2 driver and DALI-2 input devices with a BACnet BMS or any BACnet/IP or BACnet MS/TP controller. This integration aimed to make DALI devices, their data and resources, accessible from a BACnet-based control system as if they were a part of the BACnet system itself. Please refer to the new product reference for further details.



Replaced by: IN703DAL0640000

Features and benefits

- BACnet/IP client and MS/TP manager support

 Both BACnet/IP client and MS/TP manager are supported.
- Easy DALI commissioning/integration w/Intesis MAPS Integration and DALI commissioning processes are managed via the Intesis MAPS configuration tool.
- Integrated DALI power supply
 A DALI power supply is integrated into the gateway, so no
 external power supply is required.
- ✓ 10000 total signals max, 230 mA current guaranteed Up to 10,000 signals can be defined in total, with a guaranteed output current of 230 mA.

- Commissioning-friendly approach with Intesis MAPS

 Templates can be imported and reused as often as needed, significantly reducing commissioning time.
- DALI/DALI-2 drivers & DALI-2 Input devices Support DALI/DALI-2 driver, DALI-2 input device support: push buttons, absolute Eingaben, occupancy/light sensors.
- Max 64 drivers/ballasts + 64 DALI-2 input devices
 Supports up to 64 drivers/ballasts + 64 DALI-2 input devices
 (sensors/push buttons/absolute inputs).
- BACnet Advanced features calendars, schedules...

 BACnet's advanced features, such as calendars, trend logs, schedules, and more, are available.



DALI to BACnet IP & MS/TP Server gateway



| General | |
|--------------------|---------|
| Net Width (mm) | 106 |
| Net Height (mm) | 58 |
| Net Depth (mm) | 90 |
| Net Weight (g) | 194 |
| Packed Width (mm) | 127 |
| Packed Height (mm) | 86 |
| Packed Depth (mm) | 140 |
| Packed Weight (g) | 356 |
| Warranty (years) | 3 years |

Identification and Status

| Product ID | INBACDAL0640200 |
|---|-------------------------|
| Successor | IN703DAL0640000_BAC_DAL |
| Country of Origin | Spain |
| HS Code | 8517620000 |
| Dual Usage | No |
| Export Control Classification Number (ECCN) | EAR99 |

Physical Features

Contains Battery No.

Certifications and Standards


| ETIM Classification | EC001604 |
|---------------------|-------------------------------------|
| WEEE Category | IT and telecommunications equipment |





Use Case

VERSION SUPPORTING 1 DALI CHANNEL



VERSION SUPPORTING 2 DALI CHANNELS

