


Mitsubishi Electric Domestic, Mr.Slim, City Multi and Lossnay to KNX Interface with Binary Inputs

Item number: INKNXMIT001I100

The Mitsubishi Electric-KNX interface allows full bidirectional communication between Mitsubishi Electric domestic, Mr. Slim, City Multi, and Lossnay air conditioner units and KNX installations. It has four potential-free binary inputs to integrate and configure external devices (window contacts or presence detectors) to improve energy efficiency.



Mitsubishi Electric Domestic to KNX - 1 indoor unit

Features and benefits

- ✓ **ETS configuration**
The interface is configured using the ETS standard configuration tool software.
- ✓ **Multiple energy efficiency functions available**
Timeout, open window, or occupancy energy-saving functions are available to reduce energy costs.
- ✓ **Total unit control and monitoring from KNX**
Through internal variables, running hours counter (for maintenance purposes), and error indication.
- ✓ **AC unit control by both remote controller and KNX**
The AC unit can be simultaneously controlled by the manufacturer's remote controller and KNX.
- ✓ **Compatible with all KNX thermostats in the market**
All the required DPT objects to be compatible with all KNX thermostats in the market are available.
- ✓ **Smooth KNX thermostat integration**
KNX thermostats are allowed to control the AC unit via the thermostat's temperature sensor.
- ✓ **Up to five scenes saved/executed from KNX**
Up to five scenes can be saved and executed from KNX.
- ✓ **Compatibility with Lossnay and its features**
Lossnay series is supported by the interface, with horizontal vanes control and silent mode support.

Mitsubishi Electric Domestic, Mr.Slim, City Multi and Lossnay to KNX Interface with Binary Inputs



General	
Net Width (mm)	36
Net Height (mm)	21
Net Depth (mm)	59
Net Weight (g)	34
Packed Width (mm)	122
Packed Height (mm)	67
Packed Depth (mm)	93
Packed Weight (g)	165
Operating Temperature °C Min	-25
Operating Temperature °C Max	60
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Power Consumption (W)	0.232
Input Voltage (V)	29 VDC
Power Connector	2-pole
Configuration	ETS
Capacity	1 Indoor unit.
Installation Conditions	This gateway is designed to be mounted inside an enclosure. If the unit is mounted outside an enclosure, precautions should always be taken to prevent electrostatic discharge to the unit. When working inside an enclosure (e.g., making adjustments, setting switches, etc.), typical anti-static precautions should always be followed before touching the unit.
AC Model Compatibility	Mitsubishi Electric Air Conditioning

Mitsubishi Electric Domestic, Mr.Slim, City Multi and Lossnay to KNX Interface with Binary Inputs



General

Content of Delivery	Intesis Gateway, Installation Manual, AC Connection cable.
Housing Materials	Plastic
Warranty (years)	3 years
Packaging Material	Cardboard

Identification and Status

Product ID	INKNXMIT001I100
Country of Origin	Spain
HS Code	8517620000
Dual Usage	No
Export Control Classification Number (ECCN)	EAR99

Physical Features

Connectors / Input / Output	KNX, HVAC port, Binary inputs (dry contact).
LED Indicators	KNX
Contains Battery	No

Certifications and Standards

ETIM Classification	EC001604
CE	Yes
CB	Yes
UKCA	Yes
UL	Yes
KNX	Yes
WEEE Category	IT and telecommunications equipment

Mitsubishi Electric Domestic, Mr.Slim, City Multi and Lossnay to KNX Interface with Binary Inputs



Use Case

