

#### Mitsubishi Heavy Industries Domestic units to Home Automation Interface

Item number: INWMPMHI001I000

The Mitsubishi Heavy Industries gateway allows complete and natural integration of Mitsubishi Heavy Industries Domestic Air Conditioner units into IP-based Home Automation systems. The device connects to the indoor unit through a direct cable and to the Home Automation interface via Wi-Fi.



Mitsubishi Heavy Industries to Home Automation - 1 indoor

#### Features and benefits

- Intuitive web interface for Wi-Fi configuration
  Wi-Fi configuration is carried out quickly and easily through an intuitive web interface.
- Quick and easy installation

  The installation process takes only seconds; just plug in the interface and configure the Wi-Fi.
- AC unit control by remote and Home Automation

  The remote controller and the Home Automation system can control the AC unit simultaneously.
- Oriver compatibility

A wide range of compatible drivers is available on the Intesis webpage.

2,4 GHz 802.11 b/g/n Wi-Fi networks supported

Different Wi-Fi standards are supported, being compatible with 2,4 GHz 802.11 b/g/n Wi-Fi networks.

No external power required

The interface is powered directly from the AC unit, so no external power supply is required.

Open ASCII protocol

Thanks to our open ASCII protocol, integration is possible with any IP Home Automation System.



# Mitsubishi Heavy Industries Domestic units to Home Automation Interface



General	
Net Width (mm)	50
Net Height (mm)	127
Net Depth (mm)	17
Net Weight (g)	62
Packed Width (mm)	120
Packed Height (mm)	80
Packed Depth (mm)	100
Packed Weight (g)	235
Capacity	1 indoor unit.
Installation Conditions	This gateway is designed to be mounted inside an enclosure. If the unit is mounted outside an enclosure, precautions should always be taken to prevent electrostatic discharge to the unit. When working inside an enclosure (e.g., making adjustments, setting switches, etc.), typical anti-static precautions should always be followed before touching the unit.
Content of Delivery	Intesis Gateway, Installation Manual, AC Connection cable.
Warranty (years)	3 years

### Identification and Status

Product ID	INWMPMHI001I000
Country of Origin	Spain
HS Code	8517620000
Dual Usage	No
Export Control Classification Number (ECCN)	EAR99

### Physical Features

Contains Battery No

#### Certifications and Standards

ETIM Classification EC001604



# Mitsubishi Heavy Industries Domestic units to Home Automation Interface



Certifications and Standards	
CE	Yes
СВ	Yes
UL	Yes
WEEE Category	IT and telecommunications equipment



## Mitsubishi Heavy Industries Domestic units to Home Automation Interface



Integration example.

