

## Anybus X-gateway - CANopen Slave - Modbus Plus Slave

Item number: AB7896-F

The Anybus X-gateway CANopen Slave to Modbus Plus Slave enables you to connect any CANopen control system to any Modbus Plus control system. Anybus gateways ensure reliable, secure, high-speed data transfers between different industrial networks while being easy to use.



*A protocol converter that connects CANopen and Modbus Plus control systems*

### Features and benefits

- ✓ **Reach new markets**  
Target new markets using different protocols without needing to change your hardware or software, thereby decreasing your time to market and development costs.
- ✓ **Slim hardware design**  
The gateway is designed for IP20 and DIN-rail mounting, enabling you to install it with ease, close to connected devices, thereby reducing wiring requirements.
- ✓ **Easy configuration – No programming required!**  
Quickly establish the connection between the two networks with the included Anybus Configuration Manager software. No programming skills are required for the setup process.
- ✓ **Trusted partner**  
Anybus has a long history of working with all the major network organizations to ensure compliant, high-performing, and compatible products.
- ✓ **No PLC card slot needed**  
The gateway does not use a card slot in the control system, leaving room for other equipment.
- ✓ **3-year warranty**  
The gateway is designed to be robust and long-lasting. A 3-year guarantee is provided.
- ✓ **Increased PLC performance**  
The gateway allows for fast transfer of cyclic I/O data between the two networks, offloading your PLC from working with additional calculations.
- ✓ **Life cycle management**  
HMS maintains every part of the gateway, including network updates, throughout the product's lifecycle.

# Anybus X-gateway - CANopen Slave - Modbus Plus Slave



## General

Net Width (mm)	44
Net Height (mm)	127
Net Depth (mm)	114
Net Weight (g)	400
Packed Width (mm)	17
Packed Height (mm)	9
Packed Depth (mm)	19
Packed Weight (g)	600
Operating Temperature °C Min	-25
Operating Temperature °C Max	65
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Type Value at Vcc Nom (mA)	200mA @ 24V DC
Current Consumption Max value at Vcc nom (mA)	400mA @ 24V DC
Input Voltage (V)	24V DC (-20% to +20%)
Power Connector	2-pin, 5.08 Phoenix plug connector
Reverse Polarity Protection	Yes
Short Circuit Protection	Yes
Isolation	TRUE

# Anybus X-gateway - CANopen Slave - Modbus Plus Slave



## General

Mounting	DIN-rail (EN 50022 standard)
Housing Materials	Aluminium, Plastic
Packaging Material	Cardboard

## Identification and Status

Product ID	AB7896-F
Country of Origin	Sweden
HS Code	8517620000
Dual Usage	No
Export Control Classification Number (ECCN)	5A991.b.4b

## Physical Features

Connectors / Input / Output	1x D-sub 9-pin male, USB-B Config port
DIP & Rotary Switches	3x Rotary CAN Address + Baudrate
Contains Battery	No

## CANopen Features

CANopen Mode	Slave mode
CANopen Baud Rate	10 kbit/s - 1000 kbit/s
CANopen Supported Functionality	PDO, SDO;DS301 v4.02
CANopen Configuration File	EDS available
CANopen Input Data Size	512 bytes
CANopen Output Data Size	512 bytes

## Certifications and Standards

Protection Class IP	IP20
RoHS Compliant	Yes

# Anybus X-gateway - CANopen Slave - Modbus Plus Slave



## Certifications and Standards

Recycle / Disposal	TRUE
CE	Yes
FCC	No
UL	Yes
UL Information	E214107: Ord.Loc UL508, CSA C22.2 NO. 142
EMC	Yes
Environment	EN 61000-6-4, EN 55016-2-3 Class A, EN 55022 Class A, EN 61000-6-2, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6
Waste Certification (WEEE)	Yes
WEEE Category	IT and telecommunications equipment