

Anybus X-gateway – PROFIBUS Master – PROFIBUS Slave

Item number: AB7801-F

The Anybus X-gateway PROFIBUS Master to PROFIBUS Slave enables you to connect any PROFIBUS device or equipment to PROFIBUS control systems. It can be used when there is no existing PROFIBUS control system. Anybus gateways ensure reliable, secure, high-speed data transfers between different industrial networks while being easy to use.



A protocol converter that connects PROFIBUS devices to PROFIBUS PLCs

Features and benefits

✓ Reach new markets

Target new markets using different protocols without needing to change your hardware or software, thereby decreasing your time to market and development costs.

✓ Slim hardware design

The gateway is designed for IP20 and DIN-rail mounting, enabling you to install it with ease, close to connected devices, thereby reducing wiring requirements.

✓ Easy configuration – No programming required!

Quickly establish the connection between the two networks with the included Anybus Configuration Manager software. No programming skills are required for the setup process.

✓ Trusted partner

Anybus has a long history of working with all the major network organizations to ensure compliant, high-performing, and compatible products.



✓ No PLC card slot needed

The gateway does not use a card slot in the control system, leaving room for other equipment.

✓ 3-year warranty

The gateway is designed to be robust and long-lasting. A 3-year guarantee is provided.

✓ Increased PLC performance

The gateway allows for fast transfer of cyclic I/O data between the two networks, offloading your PLC from working with additional calculations.

✓ Life cycle management

HMS maintains every part of the gateway, including network updates, throughout the product's lifecycle.

Anybus X-gateway – PROFIBUS Master – PROFIBUS Slave



General

Net Width (mm)	44
Net Height (mm)	127
Net Depth (mm)	114
Net Weight (g)	400
Packed Width (mm)	17
Packed Height (mm)	9
Packed Depth (mm)	19
Packed Weight (g)	750
Operating Temperature °C Min	-25
Operating Temperature °C Max	65
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Type Value at Vcc Nom (mA)	200mA @ 24V DC
Current Consumption Max value at Vcc nom (mA)	400mA @ 24V DC
Input Voltage (V)	24V DC (-20% to +20%)
Power Connector	2-pin, 5.08 Phoenix plug connector
Reverse Polarity Protection	Yes
Short Circuit Protection	Yes
Isolation	TRUE

Anybus X-gateway – PROFIBUS Master – PROFIBUS Slave



General

Mounting	DIN-rail (EN 50022 standard)
Housing Materials	Aluminium, Plastic
Packaging Material	Cardboard

Identification and Status

Product ID	AB7801-F
Country of Origin	Sweden
HS Code	8517620000
Dual Usage	No
Export Control Classification Number (ECCN)	5A991.b.3

Physical Features

Connectors / Input / Output	1x D-sub 9-pin male and 1x D-sub 9-pin female, 1x D-sub 9-pin female PROFIBUS connector, USB-B Config port
DIP & Rotary Switches	2x Rotary Address Node
Contains Battery	No

PROFIBUS Features

PROFIBUS Mode	Master;DP Device
PROFIBUS Supported Functionality	PROFIBUS DP Master functionality according to IEC 61158;Acyclic Communication (DP-V1, Class 1 & 2);LiveList;ControlStatus, PROFIBUS-DP/DPV1 Slave functionality according to extensions of EN 50170; Acyclic Communication (DP-V1, Class 1 & 2); Acyclic User Parameter data / Diagnostics length - up to 237 bytes; Sync; Freeze; Watchdog
PROFIBUS Device Address	0-125, 0-125
PROFIBUS No. Of Devices	125
PROFIBUS Configuration File	GSD available
PROFIBUS Baud Rate	9600 bit/s - 12 Mbit/s, 9600 bit/s - 12 Mbit/s
PROFIBUS Input Data Size	512 bytes, 244 bytes (344 max tot in+out)
PROFIBUS Output Data Size	512 bytes, 244 bytes (344 max tot in+out)

Anybus X-gateway – PROFIBUS Master – PROFIBUS Slave



Certifications and Standards

Protection Class IP	IP20
RoHS Compliant	Yes
Recycle / Disposal	TRUE
CE	Yes
FCC	No
UL	Yes
UL Information	E214107: Ord.Loc UL508, CSA C22.2 NO. 142
EMC	Yes
Environment	EN 61000-6-4, EN 55016-2-3 Class A, EN 55022 Class A, EN 61000-6-2, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6
Waste Certification (WEEE)	Yes
WEEE Category	IT and telecommunications equipment