

## Anybus X-gateway – FIPIO Slave - Modbus Plus Slave

Item number: AB7878-F

The Anybus X-gateway FIPIO Slave to Modbus Plus Slave enables you to connect any FIPIO system to any Modbus Plus control system. Anybus gateways ensure reliable, secure, high-speed data transfers between different industrial networks while being easy to use.



*A protocol converter that connects FIPIO and Modbus Plus control systems*

### Features and benefits

- ✓ Reach new markets**  
 Target new markets using different protocols without needing to change your hardware or software, thereby decreasing your time to market and development costs.
- ✓ Slim hardware design**  
 The gateway is designed for IP20 and DIN-rail mounting, enabling you to install it with ease, close to connected devices, thereby reducing wiring requirements.
- ✓ Easy configuration – No programming required!**  
 Quickly establish the connection between the two networks with the included Anybus Configuration Manager software. No programming skills are required for the setup process.
- ✓ Trusted partner**  
 Anybus has a long history of working with all the major network organizations to ensure compliant, high-performing, and compatible products.
- ✓ No PLC card slot needed**  
 The gateway does not use a card slot in the control system, leaving room for other equipment.
- ✓ 3-year warranty**  
 The gateway is designed to be robust and long-lasting. A 3-year guarantee is provided.
- ✓ Increased PLC performance**  
 The gateway allows for fast transfer of cyclic I/O data between the two networks, offloading your PLC from working with additional calculations.
- ✓ Life cycle management**  
 HMS maintains every part of the gateway, including network updates, throughout the product's lifecycle.

# Anybus X-gateway – FIPIO Slave - Modbus Plus Slave



## General

Net Width (mm)	44
Net Height (mm)	127
Net Depth (mm)	114
Net Weight (g)	400
Packed Width (mm)	17
Packed Height (mm)	9
Packed Depth (mm)	19
Packed Weight (g)	600
Operating Temperature °C Min	-25
Operating Temperature °C Max	65
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Type Value at Vcc Nom (mA)	200mA @ 24V DC
Current Consumption Max value at Vcc nom (mA)	400mA @ 24V DC
Input Voltage (V)	24V DC (-20% to +20%)
Power Connector	2-pin, 5.08 Phoenix plug connector
Reverse Polarity Protection	Yes
Short Circuit Protection	Yes
Isolation	TRUE

# Anybus X-gateway – FIPIO Slave - Modbus Plus Slave



## General

Mounting	DIN-rail (EN 50022 standard)
Housing Materials	Aluminium, Plastic
Packaging Material	Cardboard

## Identification and Status

Product ID	AB7878-F
Country of Origin	Sweden
HS Code	8517620000
Dual Usage	No
Export Control Classification Number (ECCN)	5A991.b.4b

## Physical Features

Connectors / Input / Output	male 9-DSUB, USB-B Config port
DIP & Rotary Switches	2xRotary Address
Contains Battery	No

## FIPIO Features

FIPIO Supported Functionality	FIPIO Extended Device Profile (FEDP); FIPIO Class 01
FIPIO Input Data Size	64 bytes (32 words)
FIPIO Output Data Size	64 bytes (32 words)

## Certifications and Standards

Protection Class IP	IP20
RoHS Compliant	Yes
Recycle / Disposal	TRUE
CE	Yes
FCC	No

# Anybus X-gateway – FIPIO Slave - Modbus Plus Slave



## Certifications and Standards

<b>UL</b>	Yes
<b>UL Information</b>	E214107: Ord.Loc UL508, CSA C22.2 NO. 142
<b>EMC</b>	Yes
<b>Environment</b>	EN 61000-6-4, EN 55016-2-3 Class A, EN 55022 Class A, EN 61000-6-2, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6
<b>Waste Certification (WEEE)</b>	Yes
<b>WEEE Category</b>	IT and telecommunications equipment