

## Anybus X-gateway - CC-Link IE Field Slave - POWERLINK Device

Item number: AB7528-F

The Anybus X-gateway CC-Link IE Field Slave to POWERLINK Device enables you to connect any CC-Link IE Field control system to any POWERLINK control system. Anybus gateways ensure reliable, secure, high-speed data transfers between different industrial networks while being easy to use.



*A protocol converter that connects CC-Link IE Field and POWERLINK control systems*

### Features and benefits

- ✓ **Reach new markets**  
Target new markets using different protocols without needing to change your hardware or software, thereby decreasing your time to market and development costs.
- ✓ **Slim hardware design**  
The gateway is designed for IP20 and DIN-rail mounting, enabling you to install it with ease, close to connected devices, thereby reducing wiring requirements.
- ✓ **Easy configuration – No programming required!**  
Quickly establish the connection between the two networks with the included Anybus Configuration Manager software. No programming skills are required for the setup process.
- ✓ **Trusted partner**  
Anybus has a long history of working with all the major network organizations to ensure compliant, high-performing, and compatible products.
- ✓ **No PLC card slot needed**  
The gateway does not use a card slot in the control system, leaving room for other equipment.
- ✓ **3-year warranty**  
The gateway is designed to be robust and long-lasting. A 3-year guarantee is provided.
- ✓ **Increased PLC performance**  
The gateway allows for fast transfer of cyclic I/O data between the two networks, offloading your PLC from working with additional calculations.
- ✓ **Life cycle management**  
HMS maintains every part of the gateway, including network updates, throughout the product's lifecycle.

# Anybus X-gateway - CC-Link IE Field Slave - POWERLINK Device



## General

|                                                |                                    |
|------------------------------------------------|------------------------------------|
| Net Width (mm)                                 | 44                                 |
| Net Height (mm)                                | 127                                |
| Net Depth (mm)                                 | 114                                |
| Net Weight (g)                                 | 400                                |
| Packed Width (mm)                              | 17                                 |
| Packed Height (mm)                             | 9                                  |
| Packed Depth (mm)                              | 19                                 |
| Packed Weight (g)                              | 600                                |
| Operating Temperature °C Min                   | -25                                |
| Operating Temperature °C Max                   | 65                                 |
| Storage Temperature °C Min                     | -40                                |
| Storage Temperature °C Max                     | 85                                 |
| Current Consumption Type Value at Vcc Nom (mA) | 200mA @ 24V DC                     |
| Current Consumption Max value at Vcc nom (mA)  | 400mA @ 24V DC                     |
| Input Voltage (V)                              | 24V DC (-20% to +20%)              |
| Power Connector                                | 2-pin, 5.08 Phoenix plug connector |
| Reverse Polarity Protection                    | Yes                                |
| Short Circuit Protection                       | Yes                                |
| Isolation                                      | TRUE                               |

# Anybus X-gateway - CC-Link IE Field Slave - POWERLINK Device



## General

|                    |                              |
|--------------------|------------------------------|
| Mounting           | DIN-rail (EN 50022 standard) |
| Housing Materials  | Aluminium, Plastic           |
| Packaging Material | Cardboard                    |

## Identification and Status

|                                             |            |
|---------------------------------------------|------------|
| Product ID                                  | AB7528-F   |
| Country of Origin                           | Sweden     |
| HS Code                                     | 8517620000 |
| Dual Usage                                  | No         |
| Export Control Classification Number (ECCN) | 5A991.b.1  |

## Physical Features

|                             |                                      |
|-----------------------------|--------------------------------------|
| Connectors / Input / Output | 2x RJ45, USB-B Config port           |
| DIP & Rotary Switches       | 1x 8-dip switches for Station Number |
| Contains Battery            | No                                   |

## CC-Link IE Field Features

|                                          |                                                     |
|------------------------------------------|-----------------------------------------------------|
| CC-Link IE Field Mode                    | Slave                                               |
| CC-Link IE Field Supported Functionality | CC-Link IE Field Network Intelligent Device Station |
| CC-Link IE Field Bandwidth               | 1 Gbit/s fixed                                      |
| CC-Link IE Field Input Data Size         | 512 bytes                                           |
| CC-Link IE Field Output Data Size        | 512 bytes                                           |

## Certifications and Standards

|                     |      |
|---------------------|------|
| Protection Class IP | IP20 |
| RoHS Compliant      | Yes  |
| Recycle / Disposal  | TRUE |

# Anybus X-gateway - CC-Link IE Field Slave - POWERLINK Device



## Certifications and Standards

|                                   |                                                                                                                                          |
|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| <b>CE</b>                         | Yes                                                                                                                                      |
| <b>FCC</b>                        | No                                                                                                                                       |
| <b>UL</b>                         | Yes                                                                                                                                      |
| <b>UL Information</b>             | E214107: Ord.Loc UL508, CSA C22.2 NO. 142                                                                                                |
| <b>EMC</b>                        | Yes                                                                                                                                      |
| <b>Environment</b>                | EN 61000-6-4, EN 55016-2-3 Class A, EN 55022 Class A, EN 61000-6-2, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6 |
| <b>Waste Certification (WEEE)</b> | Yes                                                                                                                                      |
| <b>WEEE Category</b>              | IT and telecommunications equipment                                                                                                      |