

# Fujitsu RAC and VRF systems to Home Automation Interface (to CN connector)

### Item number: INWMPFGL001I000

The Fujitsu gateway allows complete and natural integration of Fujitsu RAC and VRF Air Conditioner units into IP-based Home Automation systems. The device connects to the indoor unit through a direct cable and to the Home Automation interface via Wi-Fi.

# Features and benefits

# Intuitive web interface for Wi-Fi configuration

Wi-Fi configuration is carried out quickly and easily through an intuitive web interface.

# Quick and easy installation

The installation process takes only seconds; just plug in the interface and configure the Wi-Fi.

# AC unit control by remote and Home Automation

The remote controller and the Home Automation system can control the AC unit simultaneously.

# Driver compatibility

A wide range of compatible drivers is available on the Intesis webpage.



#### Fujitsu to Home Automation - 1 indoor unit

# 2,4 GHz 802.11 b/g/n Wi-Fi networks supported

Different Wi-Fi standards are supported, being compatible with 2,4 GHz 802.11 b/g/n Wi-Fi networks.

# No external power required

The interface is powered directly from the AC unit, so no external power supply is required.

# Open ASCII protocol

Thanks to our open ASCII protocol, integration is possible with any IP Home Automation System.



# Fujitsu RAC and VRF systems to Home Automation Interface (to CN connector)

| General                      |  |
|------------------------------|--|
| Net Width (mm)               | 50   |
| Net Height (mm)              | 127  |
| Net Depth (mm)               | 17   |
| Net Weight (g)               | 62   |
| Packed Width (mm)            | 120  |
| Packed Height (mm)           | 80   |
| Packed Depth (mm)            | 100  |
| Packed Weight (g)            | 235  |
| Operating Temperature °C Min | 0  |
| Operating Temperature °C Max | 60   |
| Input Voltage (V)            | From the AC unit.  |
| Power Connector              | Other  |
| Capacity                     | 1 indoor unit.   |
| Installation Conditions      | This gateway is designed to be mounted inside an enclosure. If the unit is<br>mounted outside an enclosure, precautions should always be taken to prevent<br>electrostatic discharge to the unit. When working inside an enclosure (e.g.,<br>making adjustments, setting switches, etc.), typical anti-static precautions should<br>always be followed before touching the unit. |
| Content of Delivery          | Intesis Gateway, Installation Manual, AC Connection cable.   |
| Mounting                     | Wall mount   |
| Housing Materials            | Plastic  |
| Warranty (years)             | 3 years  |
| Packaging Material           | Cardboard  |



# Fujitsu RAC and VRF systems to Home Automation Interface (to CN connector)


WEEE Category

| Identification and Status                      |                 |
|--|-----------------|
| Product ID                                     | INWMPFGL001I000 |
| Country of Origin                              | Spain           |
| HS Code  | 8517620000      |
| Dual Usage                                     | No              |
| Export Control Classification<br>Number (ECCN) | EAR99           |
| Physical Features                              |                 |
| Contains Battery                               | No              |
| Certifications and Standards                   |                 |
| ETIM Classification                            | EC001604        |
| CE   | Yes             |
| СВ   | Yes             |
| UL   | Yes             |

IT and telecommunications equipment



# Fujitsu RAC and VRF systems to Home Automation Interface (to CN connector)



Integration of Fujitsu Domestic and VRF Air Conditioners Units into a Home Automation installation.

