



# Anybus Managed L2 PoE Switch

Item number: AWB5005-B

The Anybus Managed L2 PoE Switch creates robust data networks in harsh industrial settings. With Gigabit throughput, advanced configuration, diagnostics, and traffic management features, it's ideal for large networks or any application requiring high customization, control, or security. PoE simplifies installation, enhancing flexibility.



*Enhance your industrial network with Gb speed, PoE, and management features.*

## Features and benefits

- ✓ **High-Speed 10-port Gigabit switch**  
8 Gigabit PoE RJ45 ports enable efficient data and power transfer, complemented by 2 Gigabit small form-factor pluggable (SFP) ports for versatile high-speed fiber connections (100/1000M).
- ✓ **Non-blocking switch fabric**  
Efficiently handles simultaneous data transfers between all ports without bottlenecks or slowdown.
- ✓ **Layer 2 management**  
Enable reliable network operation with Layer 2 management capabilities, ensuring efficient control and optimization of your industrial network.
- ✓ **Redundancy and flexible configuration**  
Ensure network redundancy with Rapid Spanning Tree (RSTP) and enjoy flexible configuration options via GUI, CLI, or SNMP, providing versatile and user-friendly management interfaces.
- ✓ **Industrial design**  
With an IP30-rated metal housing, wide operating temperature range, and dual 24VDC booster power input, this switch ensures durable and reliable performance in harsh industrial environments.
- ✓ **Enhanced power delivery**  
Supporting 802.3at/af PoE+ standards, our switch boasts a total PoE budget of 120W, delivering a substantial 30W per port for robust and versatile power distribution.
- ✓ **Streamlined power & communication**  
Use a single cable for both power and communication with PoE (Power over Ethernet).
- ✓ **Advanced network configuration**  
Benefit from VLAN, QoS, IGMP Snooping, and LACP/Trunk support, providing advanced network configuration options for a tailored and optimized network environment.
- ✓ **DIN-Rail mounting**  
DIN-rail mounting enables you to install the switch close to connected devices, thereby reducing wiring requirements.
- ✓ **EMC Protection**  
The switch's high-level EMC protection safeguards against electromagnetic interference, critical for sensitive industrial applications.



# Anybus Managed L2 PoE Switch

## General

Net Weight (g)	1150
Packed Width (mm)	7
Packed Height (mm)	17
Packed Depth (mm)	13
Packed Weight (g)	1400
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Mounting	DIN rail mount (bracket included)
Housing Materials	Steel
Packaging Material	Cardboard
Warranty (years)	3 years

## Identification and Status

Product ID	AWB5005-B
Country of Origin	Taiwan (Province of China)
HS Code	8517620000
Dual Usage	No
Export Control Classification Number (ECCN)	5A992.c

## Physical Features

LAN Specification	8 x 10/100/1000Base-T RJ-45, PoE+ 2 x 100/1000Base SFP, DDM Store and Forward Technology with Non-Blocking Switch Fabric Auto MDI/MDIX
Contains Battery	No

## Certifications and Standards

Protection Class IP	IP30
---------------------	------



# Anybus Managed L2 PoE Switch

Certifications and Standards	
CE	Yes
Environment	EN 55016-2-3:2017 + A1:2019 EN 61000-4-2:2009 EN 61000-4-3:2006 + A1:2008 + A2:2010 EN 61000-4-4:2012 EN 61000-4-5:2014 + A1:2017 EN 61000-4-6:2014 EN 61000-4-8:2010
WEEE Category	IT and telecommunications equipment