

Anybus CompactCom Connector Board -PROFIBUS DPV1

Item number: AB6663-B

Used together with the CompactCom Brick to get quick and easy access to network connectors.



Network connectors - ready for use together with the CompactCom Brick

Features and benefits

Easy mounting

Incorporates a male strip connector - pluggable and solderable.

Modular

Mix and match CompactCom Bricks and connector boards to give your host application access to different networks.

Robust

Safe and secure mounting of the brick interface to the host PCB design.

Compatible with Starter Kit

Used together with the Anybus CompactCom Starter Kit (Brick version) to get access to the right network connectors.



Anybus CompactCom Connector Board - PROFIBUS DPV1



| General | |
|------------------------------|--|
| Net Width (mm) | 40 |
| Net Height (mm) | 16 |
| Net Depth (mm) | 39 |
| Net Weight (g) | 16 |
| Packed Weight (g) | 16 |
| Operating Temperature °C Min | -40 |
| Operating Temperature °C Max | 85 |
| Storage Temperature °C Min | -40 |
| Storage Temperature °C Max | 85 |
| Content of Delivery | Connector board |
| Not Included (in delivery) | Female strip connector, stand-off spacer |
| Mounting | PCB mounting via a customized CompactFlash connector |
| Warranty (years) | 1 |

| Identification ar | nd Status |
|-------------------|-----------|
|-------------------|-----------|

| Product ID | AB6663-B |
|---|------------|
| Country of Origin | Sweden |
| HS Code | 8517620000 |
| Dual Usage | No |
| Export Control Classification Number (ECCN) | EAR99 |

Physical Features

Connectors / Input / Output 1x 9-pin D-SUB female



Anybus CompactCom Connector Board - PROFIBUS DPV1



Physical Features

Contains Battery

No





Use Case



