

Ewon Flexy extension card - 2 serial ports

Item number: FLA3301_00

This card boosts Ewon Flexy's connectivity with 2 serial ports, enabling OEMs & system integrators to interconnect and retrieve data from serial devices. The Ewon Flexy is the link between any serial devices or PLCs and the Ethernet LAN. Compatible with Ewon Flexy 10x, 20x series and 205.



Interchangeable extension card for enhanced connectivity

Features and benefits

✓ Build your own Flexy gateway

Keep up with the evolution of communication technologies while protecting your investment in the device! The Ewon Flexy extension cards make this gateway highly modular and flexible.



Ewon Flexy extension card - 2 serial ports

General

Net Width (mm)	22
Net Height (mm)	79
Net Depth (mm)	78
Net Weight (g)	44
Packed Width (mm)	102
Packed Height (mm)	30
Packed Depth (mm)	95
Packed Weight (g)	65.5
Operating Temperature °C Min	-25
Operating Temperature °C Max	+60
Storage Temperature °C Min	-30
Storage Temperature °C Max	+70
Content of Delivery	This product consists of the following components: an electronic extension board inserted in a plastic front plate and packed in an ESD plastic bag sealed with an yellow sticker, legal references in paper version and a cardboard box.
Housing Materials	Plastic
Packaging Material	Cardboard
Warranty (years)	3

Identification and Status

Product ID	FLA3301_00
Model Code	00601
Country of Origin	Belgium



Ewon Flexy extension card - 2 serial ports

Identification and Status

HS Code	8517790000
Dual Usage	No
Export Control Classification Number (ECCN)	5A992.c

Physical Features

Connectors / Input / Output	1x RS232/485/422 port: Connector: SUBD9 (male), Physical mode: RS232/422/485, configurable by dip switch) 1x RS232 port: Connector: SUBD9 (male), Physical mode: RS232
Contains Battery	No

Certifications and Standards

CE	Yes
FCC	Yes
IC	Yes
UKCA	Yes
UL	Yes
KC	No
RCM	No
PTCRB	No
Environment	Temperature - Operating & Storage tested according to: IEC 60068-2-1 Cold test, IEC 60068-2-2 Dry heat test, IEC 60068-2-14 Change of temperature, IEC 60068-2-30 Cyclic damp heat test
Vibration and Shock	Vibration & shocks tested according to: IEC 60068-2-27 Bumps, IEC 60068-2-64 Vibration (broad-band random), IEC 60068-2-6 Vibration (sinusoidal)
Waste Certification (WEEE)	Yes
WEEE Category	IT and telecommunications equipment
Other Certification	Giteki Japan