

## Anybus CompactCom 40 Brick PROFINET-IRT

Item number: AB6675-D

The Anybus CompactCom 40 PROFINET-IRT is a communication interface that can be embedded into any industrial device or machine to enable communication with PROFINET-IRT networks. The pluggable design enables integration late in the assembly process, the addition of specific network connectors, and compliance with protection class requirements.



*Enable communication between industrial devices and PROFINET-IRT networks*

### Features and benefits

- ✓ **High performance**  
Powered by the award-winning NP40 network processor, the Anybus CompactCom guarantees fast data transfer and low latency, making it ideal for the most demanding industrial applications.
- ✓ **Quick time to market**  
HMS provides comprehensive support throughout the integration journey, ensuring a quick time to market.
- ✓ **Life cycle management**  
HMS maintains every part of the Anybus CompactCom, including network updates, throughout the product's lifecycle.
- ✓ **Fully embedded – meet IP requirements**  
The brick can be fully embedded within your product, conserving valuable space, and enabling you to provide IP class-certified protection.
- ✓ **Supports hardware changes**  
Possible to swap or install late in the manufacturing process.
- ✓ **Versatile Event-Based Hardware Interfaces**  
Enjoy fast and flexible event-based application hardware interfaces with the option to choose from 8/16-bit parallel or high-speed SPI, and I/O via the shift register interface.
- ✓ **PNO pre-certified**  
Pre-certified with PNO for network compliance, enabling faster network certification.
- ✓ **Design flexibility**  
Add your own connectors and peripherals, offering design flexibility that matches your unique needs.
- ✓ **Robust Security Measures**  
Mandatory software signatures prevent unauthorized downloads to the Anybus CompactCom, while robust encryption techniques safeguard against illicit copying.



## General

Related Accessories	AB6666-B
Net Width (mm)	36
Net Height (mm)	8
Net Depth (mm)	36
Net Weight (g)	15
Packed Width (mm)	8
Packed Height (mm)	3
Packed Depth (mm)	7
Packed Weight (g)	15
Operating Temperature °C Min	-40
Operating Temperature °C Max	85
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Class (CompactCom series)	B
Current Consumption Max value at Vcc nom (mA)	up to 500 mA
Input Voltage (V)	3.3 VDC, +/- 0.15 VDC
Application Interface	Parallel 8/16-bit (30 ns access). High speed SPI (baudrate configurable up to 50 MHz). Shift register interface (cyclical update time 82 µs). UART (for backwards compatibility with 30-series, max 625kbps).
Content of Delivery	CompactCom B40 module
Mounting	PCB mounting via pin header



## General

Warranty (years)	1 year
------------------	--------

## Identification and Status

Product ID	AB6675-D
Predecessor	AB6675-C
Country of Origin	Sweden
HS Code	8517620000
Dual Usage	No
Export Control Classification Number (ECCN)	3A991.a.2

## Physical Features

Form Factor	Brick (pluggable)
Contains Battery	No

## PROFINET Features

PROFINET Mode	Slave
PROFINET Supported Functionality	Supports RT and IRT functionality. Generic and PROFINET specific diagnostic support. SNMP agent. Web server w. customizable content. FTP server. Email client. Server Side Include (SSI) functionality. JSON functionality. PROFIenergy profile supported. PROFINET Fast Start Up. Media Redundancy Protocol (MRP). S2 system redundancy.
PROFINET Conformance Class	Class A, Class B, Class C
PROFINET Configuration File	GSDML available
PROFINET Bandwidth	10/100 Mbit/s
PROFINET Input Data Size	1440 bytes
PROFINET Output Data Size	1440 bytes

## Certifications and Standards

RoHS Compliant	Yes
UL Information	E214107