




Anybus ProfiHub B4FOR+ (Single-Mode)

Item number: 17440

The ProfiHub B4FOR+ is a cost-effective solution to link PROFIBUS fiber optic to multiple RS 485 segments and vice versa allowing ring topologies.



Redundant network expansion over long distances

Features and benefits

- ✓ **One fiber optic channel, divided into 2 ports**
Allowing creation for additional redundancy on the ring
- ✓ **Ring redundancy**
Strengthen the backbone of your network by creating additional redundancy via a ring topology
- ✓ **4 galvanically isolated channels**
Avoid daisy chained network interruptions



Anybus ProfiHub B4FOR+ (Single-Mode)

General

Net Width (mm)	111
Net Height (mm)	167
Net Depth (mm)	40
Net Weight (g)	724
Packed Width (mm)	13
Packed Height (mm)	20
Packed Depth (mm)	24
Packed Weight (g)	814
Operating Temperature °C Min	-25
Operating Temperature °C Max	70
Current Consumption Type Value at Vcc Nom (mA)	250 mA
Current Consumption Max value at Vcc nom (mA)	250 mA
Input Voltage (V)	9...31 VDC
Power Wire Diameter (mm)	< 2.5 mm ²
Reverse Polarity Protection	Yes
Warranty (years)	1 Year

Identification and Status

Product ID	17440
Country of Origin	Netherlands (the)
HS Code	8471800000

Anybus ProfiHub B4FOR+ (Single-Mode)



Identification and Status

Dual Usage	No
Export Control Classification Number (ECCN)	EAR99

Physical Features

Contains Battery	No
------------------	----

Certifications and Standards

Protection Class IP	IP20
CE	Yes
FCC	Yes
UL	Yes
WEEE Category	IT and telecommunications equipment