

Anybus ProfiHub B2F02+

Item number: 17220

The ProfiHub B2FO2+ is a cost-effective solution to link PROFIBUS fiber optic to multiple RS 485 segments and vice versa.



Simple network expansion over long distances

Features and benefits

- Fiber optic to multi RS 485 Segments

 Enable network communication over long distances
- Cost-effective solution
 One device for network extension and segmentation
- Point-to-point, bus- and star configurations

 Create a robust network backbone through segmentation and redundancy





Country of Origin

HS Code



General	
Net Width (mm)	129
Net Height (mm)	113
Net Depth (mm)	43
Net Weight (g)	592
Packed Width (mm)	16
Packed Height (mm)	6
Packed Depth (mm)	26
Packed Weight (g)	592
Operating Temperature °C Min	-25
Operating Temperature °C Max	70
Current Consumption Type Value at Vcc Nom (mA)	300 mA
Current Consumption Max value at Vcc nom (mA)	300 mA
Input Voltage (V)	931 VDC
Power Wire Diameter (mm)	< 2.5 mm ²
Reverse Polarity Protection	Yes
Warranty (years)	1 Year
Identification and Status	
Product ID	17220



Netherlands (the)

8471800000

Anybus ProfiHub B2F02+



Identification and Status

 Dual Usage
 No

 Export Control Classification Number (ECCN)
 EAR99

Physical Features

Contains Battery N

Certifications and Standards

Protection Class IP	IP20
CE	Yes
FCC	Yes
UL	Yes
WEEE Category	IT and telecommunications equipment

