

Anybus ComBricks 2 Channel Repeater

Item number: 101-201102

The Anybus 2 Channel Repeater is a standard RS 485 PROFIBUS repeater module with diagnostic LEDs and redundancy feature.

Features and benefits

Modular integration

The 2 Channel repeater is directly connected to the Head Station for immediate data availablity



A standard 2 Channel repeater to help segement your installation

Strong communication signals

The built-in 12 Mbps core ensures increased RS 485 signal strength



Anybus ComBricks 2 Channel Repeater



| General | |
|---|-----------------------------------|
| Net Weight (g) | 153 |
| Packed Width (mm) | 6 |
| Packed Height (mm) | 14 |
| Packed Depth (mm) | 20 |
| Packed Weight (g) | 275 |
| Operating Temperature °C Min | -20 |
| Operating Temperature °C Max | 60 |
| Current Consumption Type Value at Vcc Nom (mA) | 300 mA |
| Current Consumption Max value at Vcc nom (mA) | 500 mA |
| Power Wire Diameter (mm) | < 2.5 mm ² |
| Mounting | DIN rail mount (bracket included) |
| Housing Materials | Plastic |
| Packaging Material | Cardboard |
| Warranty (years) | 1 Year |

Identification and Status

| Product ID | 101-201102 |
|--|-------------------|
| Country of Origin | Netherlands (the) |
| HS Code | 8471800000 |
| Dual Usage | No |
| Export Control Classification Number (ECCN) | EAR99 |



Anybus ComBricks 2 Channel Repeater



| Physical Features | |
|------------------------------|-------------------------------------|
| Contains Battery | No |
| Certifications and Standards | |
| Protection Class IP | IP20 |
| RoHS Compliant | Yes |
| CE | Yes |
| FCC | Yes |
| UL | Yes |
| WEEE Category | IT and telecommunications equipment |

