



Anybus ProfiSwitch X5

Item number: 17030X

With the ProfiSwitch X5, you have the ability to create baudrate customization per channel without any additional configuration



Easy baudrate switching with a rotary switch

Features and benefits

- ✓ **Hot slave insertion**
install or remove the ProfiSwitch X5 during operation without any interference.
- ✓ **Adjustable baudrate per channel**
Easily integrate and extend network with different applications
- ✓ **Flexible segmentation**
The X5 is equipped with 5 isolated channels that allow star, tree or bus structured networks



Anybus ProfiSwitch X5

General

Net Width (mm)	203
Net Height (mm)	111
Net Depth (mm)	31
Net Weight (g)	822
Packed Width (mm)	16
Packed Height (mm)	6
Packed Depth (mm)	26
Packed Weight (g)	822
Operating Temperature °C Min	-25
Operating Temperature °C Max	70
Current Consumption Type Value at Vcc Nom (mA)	275 mA
Current Consumption Max value at Vcc nom (mA)	275 mA
Input Voltage (V)	12...24 VDC
Power Wire Diameter (mm)	< 2.5 mm ²
Reverse Polarity Protection	Yes
Warranty (years)	1 Year

Identification and Status

Product ID	17030X
Country of Origin	Netherlands (the)
HS Code	8471800000



Anybus ProfiSwitch X5

Identification and Status

Dual Usage	No
Export Control Classification Number (ECCN)	EAR99

Physical Features

Contains Battery	No
------------------	----

Certifications and Standards

Protection Class IP	IP20
CE	Yes
FCC	Yes
UL	Yes
WEEE Category	IT and telecommunications equipment