

Anybus CompactCom 40 Module CC-Link IE Field

Item number: AB6609-C

The Anybus CompactCom 40 CC-Link IE Field is a communication interface that can be embedded into any industrial device or machine to enable communication with CC-Link IE Field networks. The module version includes connectors to simplify installation, helping you achieve a fast time to market.



Enable communication between industrial devices and CC-Link IE Field networks

Features and benefits

✓ High performance

Powered by the award-winning NP40 network processor, the Anybus CompactCom guarantees fast data transfer and low latency, making it ideal for the most demanding industrial applications.

✓ Quick time to market

HMS provides comprehensive support throughout the integration journey, ensuring a quick time to market.

✓ Life cycle management

HMS maintains every part of the Anybus CompactCom, including network updates, throughout the product's lifecycle.

✓ Easy to install

Installing the Anybus CompactCom module is a breeze—simply slide it into the host slot. This user-friendly process can be completed by the end-user.

✓ Supports hardware changes

Possible to swap or install late in the manufacturing process.

✓ Versatile Event-Based Hardware Interfaces

Enjoy fast and flexible event-based application hardware interfaces with the option to choose from 8/16-bit parallel or high-speed SPI, and I/O via the shift register interface.

✓ CLPA pre-certified

Pre-certified with CLPA for network compliance, enabling faster network certification.

✓ Complete communication interface

The Anybus CompactCom module is a complete communication interface, equipped with connectors that simplify integration. Enjoy an all-in-one solution with easy interchangeability.

✓ Robust Security Measures

Mandatory software signatures prevent unauthorized downloads to the Anybus CompactCom, while robust encryption techniques safeguard against illicit copying.

Anybus CompactCom 40 Module CC-Link IE Field



General

Net Weight (g)	34
Packed Width (mm)	12
Packed Height (mm)	2
Packed Depth (mm)	8
Packed Weight (g)	50
Operating Temperature °C Min	-40
Operating Temperature °C Max	70
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Class (CompactCom series)	C
Input Voltage (V)	3.3 VDC, +/- 0.15 VDC
Application Interface	8/16-bit parallel (30 ns access) High speed SPI, baudrate configurable up to 20 MHz I/O (shift register interface, cyclical update time 82 µs) UART (for backwards compatibility with 30-series, max 625kbps)
Isolation	Galvanic Isolation
Content of Delivery	CompactCom M40 module
Mounting	PCB mounting via a customized CompactFlash connector
Warranty (years)	1 year

Identification and Status

Product ID	AB6609-C
Country of Origin	Sweden
HS Code	8517620000

Anybus CompactCom 40 Module CC-Link IE Field



Identification and Status

Dual Usage	No
Export Control Classification Number (ECCN)	3A991.a.2

Physical Features

Connectors / Input / Output	2x RJ45
LED Indicators	Integrated on the front. Indicates RUN and Error Status.
Form Factor	Module
Contains Battery	No