

N-Tron® 104TX Unmanaged 4-port Industrial Ethernet Switch

Item number: 104TX

The N-Tron® Unmanaged 4-port Industrial Ethernet Switch meets data gathering, control and Ethernet I/O needs cost-effectively. This plug-and-play four-port switch offers connectivity and comes in a compact, durable metal case. Top performance for high-speed layer 2 switching in demanding industrial environments.



Unmanaged 4-port industrial Ethernet switch with copper connectivity

Features and benefits

eliminating network collisions.

Gather industrial data effectively and affordably Store-and-forward technology with full wire speed communication, high throughput and minimum downtime. Upgrade existing solutions with new bandwidth by

Automatic speed and flow control Automatically negotiates and configures speed and flow control of the RJ-45 ports.

Designed for industrial settings
IP30 rating and extended environmental specifications delivers robust performance in harsh and hazardous industrial settings. Over 2 million hours MTBF.

LED status monitoring LED indicator lights display the link status and activity of each port.

Redundant DC power inputs

Redundant DC power inputs (10-30 VDC) for increased reliability. ESD and surge protection on all ports.

Four RJ-45 auto-sensing 10/100Base TX RJ-45 ports

RJ-45 ports auto sense duplex, speed and MDIX. Ethernet switching technology makes RJ-45 ports full/half duplex capable.

Metal DIN-rail enclosure
Comes in a 35mm DIN-rail mountable hardened metal case.
Compact design with a small footprint. Dimensions: 7.3 cm
X 3.8 cm X 9.0 cm.

MAC address support Connect to advanced and complex network architectures with support for up to 2,000 MAC addresses.

✓ Leading industry certifications for industrial environments IEEE 802.3 compliant. Certified UL Class I, Division 2 rating and CE approval. EN 50155 Rail and ABS Type approval for shipboard applications. Operating temperature of -40 °C to 80 °C.



N-Tron® 104TX Unmanaged 4-port Industrial Ethernet Switch



General	
Net Weight (g)	454
Packed Width (mm)	152.4
Packed Height (mm)	101.6
Packed Depth (mm)	203.2
Packed Weight (g)	900
Operating Temperature °C Min	-40
Operating Temperature °C Max	80
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Relative Humidity	10% to 95% (Non Condensing)
Power Consumption (W)	5.16
Input Voltage (V)	10-30 VDC
Maximum Installation Altitude (m)	3048
Mounting	DIN rail mount (bracket included)
Housing Materials	Metal Housing
Packaging Material	Cardboard
Warranty (years)	3
Identification and Status	
Product ID	104TX
Country of Origin	United States of America (the)



N-Tron® 104TX Unmanaged 4-port Industrial Ethernet Switch



Identification and Status

HS Code	8517620000
Dual Usage	No
Export Control Classification Number (ECCN)	EAR99

Physical Features

Connectors / Input / Output	4x RJ45
Top Wiring Clearance (mm)	25.4
Front Wiring Clearance (mm)	50.8
SD Card Slot	No
Flash Drive	No
Contains Battery	No

Bluetooth Features

Net Data Throughput Up to 800 Mb/s

Certifications and Standards

RoHS Compliant	Yes
CE	Yes
FCC	Yes
UKCA	No
UL	Yes
ATEX	No
DNV	Yes
КС	No
Mean Time Before Failure (MTBF)	>2,000,000 hours

