

N-Tron® NT5016 16 Port Gigabit Managed Industrial Ethernet Switch

Item number: NT-5016-000-0000

The N-Tron NT5016 is a managed Ethernet switch that keeps networks connected and protected right out of the box. Easy to use and highly reliable, it optimizes communication performance and maximizes uptime. It features sixteen 10/100/1000BaseT RJ45 ports and the rugged design and security of the N-Tron 5000 series.



Connects your devices reliably with simple configuration and robust security

Features and benefits

Rugged and durable design

Operates in extreme temperatures from -40° C to 80° C, has high shock and vibration tolerance, ESD and surge protection. Built to provide years of reliable performance in harsh conditions.

Easy setup with configuration wizard

A quick start wizard walks administrators through switch configuration for fast deployment. Retrieve and redistribute configuration files easily to other NT5000 devices on the network.

High quality graphical user interface

Intuitive and user-friendly dashboard features color-coded gauges, making it easy to monitor and manage activity. View port configuration and activity, traffic, event logs, errors and more.

Designed with network redundancy to maximize uptime

High availability protocols (STP/RSTP/MSTP), port trunking and LACP maximize uptime and keep mission critical operations running without interruption.

Design enhancements to simplify VLAN configuration

Ease of use enhancements make VLAN configurations easier than ever. The graphical display shows a logical view of the switch, including the VLAN port and tag configuration.

Advanced features designed to meet future needs

With advanced management, performance and security features provided right out of the box, you have tools you need now – and as your network needs grow.

Extensive industry certifications

With extensive compliance certifications, the switch is ideal for a wide range of industrial applications in factory automation, oil and gas, water/wastewater, power utilities and more.

Reliable connectivity to industrial data

The N-Tron NT5000 managed Ethernet switch connects industrial operations to data reliably and efficiently. It provides an industry-ready way to move data across industrial networks.

Robust securty for your network switches

Protect against unauthorized access with built-in security features: password encryption, IEEE 802.1X port and user authentication (RADIUS), MAC security and support for event logs and syslogs.

~30ms healing and RSTP/MSTP network redundancy

Comes with N-Tron's N-Ring ~30ms healing technology. Preconfigured N-Ring ports make it easy to add new NT5000series switches. Reconfigure by changing the ring from "auto-member" to "manager."

N-View[™] 2 monitoring technology

Monitor multiple N-View[™]-capable switches from a single window. This windows-based software reduces downtime by centralizing firmware management, grouping devices and scheduling firmware updates.



N-Tron® NT5016 16 Port Gigabit Managed Industrial Ethernet Switch



General	
Net Weight (g)	0.01
Packed Width (mm)	254
Packed Height (mm)	133.35
Packed Depth (mm)	304.8
Packed Weight (g)	962.01
Operating Temperature °C Min	-40
Operating Temperature °C Max	80
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Relative Humidity	10% to 95% (Non Condensing)
Input Voltage (V)	10-49 VDC
Maximum Installation Altitude (m)	3048
Mounting	DIN rail mount (bracket included), Wall mount
Panel Cut-Out Dimensions	97.8 x 3.74" (95.1 mm)
Housing Materials	Metal Housing
Packaging Material	Cardboard
Warranty (years)	3

Identification and Status		
Product ID	NT-5016-000-0000	
Country of Origin	United States of America (the)	



N-Tron® NT5016 16 Port Gigabit Managed Industrial Ethernet Switch



Identification and Status		
HS Code	8517620000	
Dual Usage	No	
Export Control Classification Number (ECCN)	EAR99	
Physical Features		
Top Wiring Clearance (mm)	101.6	
Front Wiring Clearance (mm)	50.8	
LAN Specification	up to 4k	
SD Card Slot	No	
Flash Drive	No	
Contains Battery	No	
Bluetooth Features		
Bluetooth Featur	Tes l	
Bluetooth Featur Net Data Throughput	Up to 32.0 Gb/s	
	Up to 32.0 Gb/s	
Net Data Throughput	Up to 32.0 Gb/s	
Net Data Throughput Certifications an	up to 32.0 Gb/s d Standards	
Net Data Throughput Certifications an Protection Class IP	Up to 32.0 Gb/s d Standards IP20	
Net Data Throughput Certifications an Protection Class IP RoHS Compliant	Up to 32.0 Gb/s d Standards IP20 Yes	
Net Data Throughput Certifications an Protection Class IP RoHS Compliant CE	Up to 32.0 Gb/s d Standards IP20 Yes Yes	
Net Data Throughput Certifications an Protection Class IP RoHS Compliant CE FCC	Up to 32.0 Gb/s d Standards IP20 Yes Yes Yes	
Net Data Throughput Certifications and Protection Class IP RoHS Compliant CE FCC UKCA	Up to 32.0 Gb/s d Standards IP20 Yes Yes Yes Yes	
Net Data Throughput Certifications and Protection Class IP RoHS Compliant CE FCC UKCA UL	Up to 32.0 Gb/s d Standards IP20 Yes Yes Yes Yes No	



N-Tron® NT5016 16 Port Gigabit Managed Industrial Ethernet Switch



Certifications and Standards

Mean Time Before Failure (MTBF)	1.2M Hours
Vibration and Shock	IEC 68-2-27: 200 g @ 10 ms Triaxial; non-operational; panel mounted; IEC 68-2-6: 15 g @ 5-200 Hz Triaxial; operational; panel mounted

