

N -Tron® 708FX2-SC Managed 8-port Industrial Ethernet Switch

Item number: 708FX2-SC

The N -Tron® 8-port Managed Industrial Ethernet Switch is a powerful and durable solution to connect Ethernet-enabled equipment. Best-in-class network management features for remote monitoring and configuration control. High performance, reliability and noise immunity for rugged industrial applications. Six copper 10/100 ports + two 100Base 2km, multimode fiber ports with SC connectors.



Durable and high-performing 8-port managed Ethernet switch for industrial connectivity

Features and benefits

- ✓ **Easily connect and manage Ethernet-enabled devices**
Store-and-forward technology and superior switch performance in industrial applications where ruggedness and extended distances are required.
- ✓ **Flexibility with both copper and fiber ports**
Six 10/100BaseTX RJ-45 ports and two multimode 100BaseFX fiber optic ports with SC connectors.
- ✓ **Easy to configure management functionality**
Fully managed features are easily configurable from a web browser. Set up SNMP, VLAN, Quality of Service (QoS), port trunking, port mirroring, IGMP, SNMP and RSTP to your specifications.
- ✓ **Switch status monitoring and LED indicators**
LED indicators are configurable to indicate power failure and N-Ring status.
- ✓ **Real-time remote monitoring**
N-View™ Windows-based software provides remote monitoring.
- ✓ **Enhanced Port Security**
Port-based MAC address filtering delivers a high level of security to your network connections. Supports up to 8,000 MAC addresses.
- ✓ **Designed for rugged environments**
Hardened metal DIN-rail enclosure delivers top performance in demanding environments. High shock and vibration ratings. Case dimensions: 2.3" X 6.0" X 3.8".
- ✓ **Easy to use and flexible 10/100BaseTX ports**
Auto-sensing for duplex and MDIX. Auto-configurable for maximum speed by default. Can also be hard coded. Wire speed capability on all 10/100BaseTX ports.
- ✓ **DHCP Server for Automatic IP address assignment**
DHCP Server assigns IP addresses automatically. Includes DHCP Option 82 relay, Option 61 and IP fallback.
- ✓ **Leading certifications for industrial environments**
IEEE 1613 compliance. Suitable for hazardous environments with UL Class I, Division 2 listing and CE certifications. Over 2 million hours MTBF and operating temperature of -40 °C to 85 °C.
- ✓ **N -Ring™ technology with ~30ms healing time**
N-Ring™ technology offers expanded ring size capacity to support up to 250 N-Tron managed switches. The ring manager provides complete fault diagnostics and ring health status via browser.
- ✓ **Redundant power inputs and surge protection**
Redundant power input (10-30 VDC). ESD and surge protection diodes on all ports.

N-Tron® 708FX2-SC Managed 8-port Industrial Ethernet Switch



General

Net Weight (g)	750
Packed Width (mm)	215.9
Packed Height (mm)	127
Packed Depth (mm)	215.9
Packed Weight (g)	1361
Operating Temperature °C Min	-40
Operating Temperature °C Max	85
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Relative Humidity	5% to 95% (Non Condensing)
Input Voltage (V)	10-30 VDC
Maximum Installation Altitude (m)	3048
Mounting	DIN rail mount (bracket included)
Housing Materials	Metal Housing
Packaging Material	Cardboard
Warranty (years)	3

Identification and Status

Product ID	708FX2-SC
Country of Origin	United States of America (the)
HS Code	8517620000

N-Tron® 708FX2-SC Managed 8-port Industrial Ethernet Switch



Identification and Status

Dual Usage	No
Export Control Classification Number (ECCN)	EAR99

Physical Features

Connectors / Input / Output	6x RJ45, 2x SC
Top Wiring Clearance (mm)	25.4
Front Wiring Clearance (mm)	101.6
Contains Battery	No

Certifications and Standards

RoHS Compliant	Yes
CE	Yes
FCC	Yes
UKCA	No
UL	Yes
ATEX	Yes
DNV	Yes
KC	No
Mean Time Before Failure (MTBF)	>2 million
Vibration and Shock	Shock: 200g @ 10ms; Vibration: 50g, 5-200Hz, Triaxial