



Sixnet® SLX-10MG-1

Managed 10-port Industrial Ethernet Switch

Item number: SLX-10MG-1

The Sixnet® 10-port Managed Industrial Ethernet Switch enables fast Ethernet connectivity for industrial equipment in extreme industrial settings. Rugged and high-performing with a range of advanced control, monitoring and security features deployable through a web browser. Seven 10/100BaseTX RJ-45 ports, one 10/100BaseTX RJ-45 port, and two dual-mode SFP combo slots (100Base or 1000Base).



High-speed 10-port managed Ethernet switch for industrial connectivity

Features and benefits

- ✓ **Easily connect and manage Ethernet-enabled devices**
Deliver outstanding switch performance to maritime, oil & gas, transportation, utility and energy applications. Well suited for use as a fiber optic ring manager or an aggregation switch.
- ✓ **Engineered for rugged environments**
Durable, hardened metal DIN-rail mountable enclosures offer extended shock and vibration protection and electrical noise and surge immunity. Suitable for the most demanding industrial environments.
- ✓ **Copper and fiber capability via 10 total ports**
Connect devices to up to 10 ports, including seven 10/100BaseTX copper ports, one 10/100/100Base TX copper port and two dual-mode SFP combo ports that support 100Base or 1000 Base fiber transceivers. SFP transceivers sold separate.
- ✓ **High-performing Ethernet ports**
Auto-sensing for speed, flow and MDIX. Ethernet switching technology makes RJ-45 ports full/half duplex capable.
- ✓ **User-configurable advanced functionality**
Features are easily configurable from a web browser or CLI management. Set up RSTP/MSTP, VLAN, priority queuing, IGMP, SNMP, RMON and port mirroring to your specifications.
- ✓ **Intelligent Ethernet routing**
Route Ethernet messages only out the appropriate port and enable priority queuing (QoS/CoS/DS). Broadcast and multicast with storm protection.
- ✓ **Real-Time Ring technology and RSTP/MSTP**
Real-Time Ring technology and Rapid Spanning Tree Protocol (RSTP)/Multiple Spanning Tree Protocol (MSTP) provide network redundancy. Monitor ring and spanning tree health status via web browser.
- ✓ **Alarm and status monitoring**
Stay informed about switch health and power using LED status indicators and configurable alarm output.
- ✓ **Leading certifications for industrial environments**
IEEE 802.3 compliance. Suitable for hazardous environments with UL Class I, Division 2 listing and CE and CSA certifications. ABS Type approval for shipboard applications. Over 1 million hours MTBF and operating temperature of -40 °C to 75 °C.
- ✓ **Remote monitoring with Modbus/TCP**
Monitor power, port and ring status through a web browser in real time using Modbus/TCP monitoring.
- ✓ **Enhanced port security**
Port-based MAC address filtering and HTTPS, SSH, SSL and SNMPv3 protocols deliver a high level of security to your network connections. Supports up to 8192 MAC addresses.
- ✓ **Redundant power inputs and surge protection**
Dual redundant power inputs (10-30 VDC) with surge protection.

Sixnet® SLX-10MG-1 Managed 10-port Industrial Ethernet Switch



General

Net Weight (g)	589.6696
Packed Weight (g)	1179.6696
Operating Temperature °C Min	-40
Operating Temperature °C Max	75
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Relative Humidity	5% to 95% (non condensing)
Power Consumption (W)	0
Input Voltage (V)	10-30 VDC
Maximum Installation Altitude (m)	9144
Mounting	DIN rail mount (bracket included)
Housing Materials	Aluminium
Packaging Material	Cardboard
Warranty (years)	5

Identification and Status

Product ID	SLX-10MG-1
Country of Origin	Taiwan (Province of China)
HS Code	8517620000
Dual Usage	No
Export Control Classification Number (ECCN)	EAR99

Sixnet® SLX-10MG-1 Managed 10-port Industrial Ethernet Switch



Physical Features

Top Wiring Clearance (mm)	102
Front Wiring Clearance (mm)	102
SD Card Slot	No
Flash Drive	No
Contains Battery	No

Bluetooth Features

Net Data Throughput	Up to 7.4 Gb/s
---------------------	----------------

Certifications and Standards

Protection Class IP	IP40
RoHS Compliant	Yes
CE	Yes
FCC	Yes
UKCA	No
UL	Yes
ATEX	Yes
DNV	No
KC	No
Mean Time Before Failure (MTBF)	>1M+ Hours
Vibration and Shock	Shock: IEC 60068-2-6 and -27; Vibration: IEC 60068-2-6 and -27