



# Sixnet® SL-6ES-4ST

## Unmanaged 6-port Industrial Ethernet Switch

Item number: SL-6ES-4ST

The Sixnet® 6-port Unmanaged Industrial Ethernet Switch is plug and play to help you save time and reduce costs. Ruggedized design is engineered to last and offers superior performance in industrial settings. Get fast, reliable connectivity for your applications through four 10/100BaseTX RJ-45 ports and two 100BaseFX multimode 4km fiber ports with ST connectors.



*Plug-and-play 6-port unmanaged Ethernet switch for real-time operation*

## Features and benefits

- ✓ **Real-time operation with ultimate simplicity**  
Deliver fast, real-time deterministic switch operation to your industrial network right out of the box. No complicated setup involved.
- ✓ **Flexible port configuration**  
Connect devices to up to 6 ports, including 4 fast 10/100BaseTX copper ports and 2 noise-immune 100BaseFX multimode 4km fiber ports with ST connectors.
- ✓ **High-performing Ethernet ports**  
Unmanaged operation with automatic speed, flow and MDI/MDIX control. Supports full/half duplex operation and TD/RD auto-polarity.
- ✓ **Durable case with IP30 protection**  
Easy to install and built to last. Comes in a durable IP30-rated Lexan case for DIN-rail or direct to panel mounting.
- ✓ **Ideal for light-to-moderate industrial applications**  
Designed for superior performance with surge and spike protected circuitry for trouble-free operation. Ultra-reliable with over 1 million hours MTBF.
- ✓ **LED status monitoring**  
LED indicator lights display Ethernet link connectivity and activity status.
- ✓ **Leading certifications for industrial environments**  
IEEE 802.3 compliance. Suitable for hazardous environments with UL Class I, Division 2 listing and CE and CSA certifications. ABS Type approval for shipboard applications. Operating temperature of -40 °C to 60 °C.
- ✓ **Redundant power inputs**  
Dual redundant power inputs (10-30 VDC).

# Sixnet® SL-6ES-4ST Unmanaged 6-port Industrial Ethernet Switch



## General

Net Weight (g)	295
Packed Weight (g)	295
Operating Temperature °C Min	-40
Operating Temperature °C Max	60
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Relative Humidity	5% to 95% (non condensing)
Power Consumption (W)	0
Input Voltage (V)	10-30 VDC
Mounting	DIN rail mount (bracket included)
Housing Materials	Plastic
Packaging Material	Cardboard
Warranty (years)	5

## Identification and Status

Product ID	SL-6ES-4ST
Country of Origin	Taiwan (Province of China)
HS Code	8517620000
Dual Usage	No

## Physical Features

SD Card Slot	No
Flash Drive	No

# Sixnet® SL-6ES-4ST Unmanaged 6-port Industrial Ethernet Switch



## Physical Features

Contains Battery	No
------------------	----

## Certifications and Standards

Protection Class IP	IP30
RoHS Compliant	Yes
CE	Yes
FCC	Yes
UKCA	No
UL	Yes
ATEX	Yes
DNV	No
KC	No
Mean Time Before Failure (MTBF)	>1 million
Vibration and Shock	Shock: IEC60068-2-27; Vibration: IEC 60068-2-6 and -27