



N -Tron® 716FXE2-SC-80 Managed 16-port Industrial Ethernet Switch

Item number: 716FXE2-SC-80

The N -Tron® 16-port Managed Industrial Ethernet Switch is a powerful and durable solution to connect Ethernet-enabled equipment. Best-in-class network management features for remote monitoring and configuration control. High performance, reliability and noise immunity for rugged industrial applications. Sixteen copper 10/100 ports + two 100Base 80km, singlemode fiber ports with SC connector.

Durable and high-performing 16-port managed Ethernet switch for industrial connectivity

Features and benefits

- Easily connect and manage Ethernet-enabled devices

 Store-and-forward technology and superior switch performance in industrial applications where ruggedness and extended distances are required.
- Flexibility with both copper and fiber ports

 Fourteen 10/100BaseTX RJ-45 ports and two singlemode

 100BaseFX fiber optic ports with SC connectors.
- Easy to configure management functionality
 Fully managed features are easily configurable from a web browser. Set up SNMP, VLAN, Quality of Service (QoS), port trunking, port mirroring, IGMP, SNMP and RSTP to your specifications.
- Switch status monitoring and LED indicators
 LED indicators are configurable to indicate power failure and N-Ring status.
- Real-time remote monitoring
 N-View™ Windows-based software provides remote monitoring.
- Enhanced Port Security
 Port-based MAC address filtering delivers a high level of security to your network connections. Supports up to 8,000 MAC addresses.

- Designed for rugged environments

 Hardened metal DIN-rail enclosure delivers top performance in demanding environments. High shock and vibration ratings. Case dimensions: 2.3" X 8.3" X 4.8".
- ✓ Easy to use and flexible 10/100BaseTX ports

 Auto-sensing for duplex and MDIX. Auto-configurable for maximum speed by default. Can also be hard coded. Wire speed capability on all 10/100BaseTX ports.
- DHCP Server for Automatic IP address assignment

 DHCP Server assigns IP addresses automatically. Includes

 DHCP Option 82 relay, Option 61 and IP fallback.
- ✓ Leading certifications for industrial environments

 IEEE 1613 compliance. Suitable for hazardous environments with UL Class I, Division 2 listing and CE certifications. Over 2 million hours MTBF and operating temperature of -40 °C to 70 °C.
- N -Ring™ technology with ~30ms healing time
 N-Ring™ technology offers expanded ring size capacity to support up to 250 N-Tron managed switches. The ring manager provides complete fault diagnostics and ring health status via browser.
- Redundant power inputs and surge protection

 Redundant power input (10-30 VDC). ESD and surge protection diodes on all ports.



N -Tron® 716FXE2-SC-80 Managed 16-port Industrial Ethernet Switch



General	
Net Weight (g)	2038.5
Packed Weight (g)	2038.5
Identification and Status	
Product ID	716FXE2-SC-80
Country of Origin	United States of America (the)
HS Code	8517620000
Dual Usage	No
Physical Features	
Contains Battery	No

