



# N -Tron® 711FXE3-ST-80-HV

## Managed 11-port Industrial Ethernet Switch

**Item number: 711FXE3-ST-80-HV**

The N -Tron® 11-port Managed Industrial Ethernet Switch is a powerful and durable solution to connect Ethernet-enabled equipment. Best-in-class network management features for remote monitoring and configuration control. High performance, reliability and noise immunity for rugged industrial applications. Eight copper 10/100 ports + three 100Base 80km, singlemode fiber ports with ST connector.

*Durable and high-performing 11-port managed Ethernet switch for industrial connectivity*

### Features and benefits

- ✓ **Easily connect and manage Ethernet-enabled devices**  
Store-and-forward technology and superior switch performance in industrial applications where ruggedness and extended distances are required.
- ✓ **Flexibility with both copper and fiber ports**  
Eight 10/100BaseTX RJ-45 ports and three singlemode 100BaseFX fiber optic ports with ST connectors.
- ✓ **Easy to configure management functionality**  
Fully managed features are easily configurable from a web browser. Set up SNMP, VLAN, Quality of Service (QoS), port trunking, port mirroring, IGMP, SNMP and RSTP to your specifications.
- ✓ **Switch status monitoring and LED indicators**  
LED indicators are configurable to indicate power failure and N-Ring status.
- ✓ **Real-time remote monitoring**  
N-View™ Windows-based software provides remote monitoring.
- ✓ **Enhanced Port Security**  
Port-based MAC address filtering delivers a high level of security to your network connections. Supports up to 8,000 MAC addresses.
- ✓ **Designed for rugged environments**  
Hardened metal DIN-rail enclosure delivers top performance in demanding environments. High shock and vibration ratings. Case dimensions: 4.3" X 2.4" X 4.6".
- ✓ **Easy to use and flexible 10/100BaseTX ports**  
Auto-sensing for duplex and MDIX. Auto-configurable for maximum speed by default. Can also be hard coded. Wire speed capability on all 10/100BaseTX ports.
- ✓ **DHCP Server for Automatic IP address assignment**  
DHCP Server assigns IP addresses automatically. Includes DHCP Option 82 relay, Option 61 and IP fallback.
- ✓ **Leading certifications for industrial environments**  
IEEE 1613 compliance. Suitable for hazardous environments with UL Class I, Division 2 listing and CE certifications. Over 2 million hours MTBF and operating temperature of -40 °C to 70 °C.
- ✓ **N -Ring™ technology with ~30ms healing time**  
N-Ring™ technology offers expanded ring size capacity to support up to 250 N-Tron managed switches. The ring manager provides complete fault diagnostics and ring health status via browser.
- ✓ **Redundant power inputs and surge protection**  
Redundant power input (43-300 VDC). ESD and surge protection diodes on all ports.

# N-Tron® 711FXE3-ST-80-HV Managed 11-port Industrial Ethernet Switch



## General

Net Weight (g)	1132.5
Packed Weight (g)	1132.5
Operating Temperature °C Min	-40
Operating Temperature °C Max	70
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Relative Humidity	5% to 95% (Non Condensing)
Input Voltage (V)	43-300 VDC
Maximum Installation Altitude (m)	3048
Mounting	DIN rail mount (bracket included)
Housing Materials	Metal Housing
Packaging Material	Cardboard
Warranty (years)	3

## Identification and Status

Product ID	711FXE3-ST-80-HV
Country of Origin	United States of America (the)
HS Code	8517620000
Dual Usage	No

## Physical Features

Connectors / Input / Output	8x RJ45, 3x ST
Top Wiring Clearance (mm)	26

# N -Tron® 711FXE3-ST-80-HV Managed 11-port Industrial Ethernet Switch



## Physical Features

Front Wiring Clearance (mm)	51
Contains Battery	No

## Certifications and Standards

RoHS Compliant	Yes
CE	Yes
FCC	Yes
UKCA	No
UL	No
ATEX	No
DNV	No
KC	No
Mean Time Before Failure (MTBF)	>2 million
Vibration and Shock	Shock: 50g @ 10ms; Vibration: 30g, 10-200Hz, Triaxial