



N -Tron® 710FX2-SC-HV Managed 10-port Industrial Ethernet Switch

Item number: 710FX2-SC-HV

The N -Tron® 10-port Managed Industrial Ethernet Switch is a powerful and durable solution to connect Ethernet-enabled equipment. Best-in-class network management features for remote monitoring and configuration control. High performance, reliability and noise immunity for rugged industrial applications. Eight copper 10/100 ports + two 100Base 2km, multimode fiber ports with SC connector.

Durable and high-performing 10-port managed Ethernet switch for industrial connectivity

Features and benefits

- ✓ **Easily connect and manage Ethernet-enabled devices**
Store-and-forward technology and superior switch performance in industrial applications where ruggedness and extended distances are required.
- ✓ **Flexibility with both copper and fiber ports**
Eight 10/100BaseTX RJ-45 ports and two multimode 100BaseFX fiber optic ports with SC connectors.
- ✓ **Easy to configure management functionality**
Fully managed features are easily configurable from a web browser. Set up SNMP, VLAN, Quality of Service (QoS), port trunking, port mirroring, IGMP, SNMP and RSTP to your specifications.
- ✓ **Switch status monitoring and LED indicators**
LED indicators are configurable to indicate power failure and N-Ring status.
- ✓ **Real-time remote monitoring**
N-View™ Windows-based software provides remote monitoring.
- ✓ **Enhanced Port Security**
Port-based MAC address filtering delivers a high level of security to your network connections. Supports up to 8,000 MAC addresses.
- ✓ **Designed for rugged environments**
Hardened metal DIN-rail enclosure delivers top performance in demanding environments. High shock and vibration ratings. Case dimensions: 4.3" X 2.4" X 4.6".
- ✓ **Easy to use and flexible 10/100BaseTX ports**
Auto-sensing for duplex and MDIX. Auto-configurable for maximum speed by default. Can also be hard coded. Wire speed capability on all 10/100BaseTX ports.
- ✓ **DHCP Server for Automatic IP address assignment**
DHCP Server assigns IP addresses automatically. Includes DHCP Option 82 relay, Option 61 and IP fallback.
- ✓ **Leading certifications for industrial environments**
IEEE 1613 compliance. Suitable for hazardous environments with UL Class I, Division 2 listing and CE certifications. Over 2 million hours MTBF and operating temperature of -40 °C to 70 °C.
- ✓ **N -Ring™ technology with ~30ms healing time**
N-Ring™ technology offers expanded ring size capacity to support up to 250 N-Tron managed switches. The ring manager provides complete fault diagnostics and ring health status via browser.
- ✓ **Redundant power inputs and surge protection**
Redundant power input (43-300 VDC). ESD and surge protection diodes on all ports.

N-Tron® 710FX2-SC-HV Managed 10-port Industrial Ethernet Switch



| General | |
|-----------------------------------|-----------------------------------|
| Net Weight (g) | 1132.5 |
| Packed Weight (g) | 1132.5 |
| Operating Temperature °C Min | -40 |
| Operating Temperature °C Max | 70 |
| Storage Temperature °C Min | -40 |
| Storage Temperature °C Max | 85 |
| Relative Humidity | 5% to 95% (Non Condensing) |
| Input Voltage (V) | 43-300 VDC |
| Maximum Installation Altitude (m) | 3048 |
| Mounting | DIN rail mount (bracket included) |
| Housing Materials | Metal Housing |
| Packaging Material | Cardboard |
| Warranty (years) | 3 |

| Identification and Status | |
|---------------------------|--------------------------------|
| Product ID | 710FX2-SC-HV |
| Country of Origin | United States of America (the) |
| HS Code | 8517620000 |
| Dual Usage | No |

| Physical Features | |
|-----------------------------|----------------|
| Connectors / Input / Output | 8x RJ45, 1x SC |
| Top Wiring Clearance (mm) | 26 |

N-Tron® 710FX2-SC-HV Managed 10-port Industrial Ethernet Switch



Physical Features

| | |
|-----------------------------|----|
| Front Wiring Clearance (mm) | 51 |
| Contains Battery | No |

Certifications and Standards

| | |
|---------------------------------|---|
| RoHS Compliant | Yes |
| CE | Yes |
| FCC | Yes |
| UKCA | No |
| UL | No |
| ATEX | No |
| DNV | No |
| KC | No |
| Mean Time Before Failure (MTBF) | >2 million |
| Vibration and Shock | Shock: 50g @ 10ms; Vibration: 30g, 10-200Hz, Triaxial |