

N-Tron® 1003GX2-LX-40 Unmanaged 3-port Gigabit Industrial Ethernet Switch

Item number: 1003GX2-LX-40

The N-Tron® Unmanaged 3-port Gigabit Industrial Ethernet Switch meets data acquisition needs easily. Durable metal case has a compact footprint. Plug-and-play operation makes setup easy. Uncompromising performance for high-speed layer 2 switching in harsh industrial environments. One 10/100/1000 BaseT RJ-45 port + two 1000BaseLX singlemode, 40km SFP transceivers.



Ruggedized unmanaged gigabit switch for data acquisition with 2 NTSFP-LX-40 singlemode fiber transceivers

Features and benefits

- ✓ **Reliable data communication in harsh settings**
Store-and-forward technology with full wire speed communication. Ideal for mission-critical data acquisition, security surveillance, control and Ethernet I/O applications.
- ✓ **Automatic speed control and duplex operation for RJ-45 port**
Built-in RJ45 port with MDIX auto cable sensing, speed automation and flow control, as well as full/half duplex operation. Maximum switch throughput up to 6.0 Gb/s.
- ✓ **Designed for harsh environments**
Uncompromising performance and maximum uptime in extreme industrial settings. Operating temperature of -40 °C to 85 °C. Over 2M hours MTBF.
- ✓ **LED status monitoring**
LED indicator lights display the link status and activity of each port.
- ✓ **Redundant power inputs**
Redundant power inputs (10-30 VDC) with built-in surge protection.
- ✓ **Connectivity through three Gigabit ports**
Auto-sensing Gigabit ports for copper and fiber connectivity. One 10/100/1000BaseT RJ-45 port and two 1000BaseLX fiber SFP transceiver ports.
- ✓ **Compact, ruggedized DIN-rail mountable enclosure**
Housed in a rugged 35mm DIN-rail mountable metal enclosure. Compact and space-saving design for easy installation. Case dimensions: 10.2cm x 2.6cm x 9.4cm.
- ✓ **Secure access control with MAC address support**
Supports up to 1,024 MAC addresses.
- ✓ **Leading compliance certifications**
Certified UL Class I, Division 2 rating and CE approval. IEEE 1613, IEEE 802.3, 802.3u, 802.3z and 802.3ab and ABS compliant. Extended environmental specifications.

N-Tron® 1003GX2-LX-40 Unmanaged 3-port Gigabit Industrial Ethernet Switch



General

Net Weight (g)	770.1
Packed Weight (g)	770.1
Operating Temperature °C Min	-40
Operating Temperature °C Max	85
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Relative Humidity	10% to 95% (Non Condensing)
Input Voltage (V)	10-30 VDC
Maximum Installation Altitude (m)	3048
Mounting	DIN rail mount (bracket included)
Housing Materials	Metal Housing
Packaging Material	Cardboard
Warranty (years)	3

Identification and Status

Product ID	1003GX2-LX-40
Country of Origin	United States of America (the)
HS Code	8517620000
Dual Usage	No

Physical Features

Connectors / Input / Output	1x RJ45, 2x SFP LC Duplex Gigaabit Fiber Ports
Top Wiring Clearance (mm)	25.4

N-Tron® 1003GX2-LX-40 Unmanaged 3-port Gigabit Industrial Ethernet Switch



Physical Features

Front Wiring Clearance (mm)	101.6
SD Card Slot	No
Flash Drive	No
Contains Battery	No

Bluetooth Features

Net Data Throughput	Up to 6.0 Gb/s
---------------------	----------------

Certifications and Standards

RoHS Compliant	Yes
CE	Yes
FCC	Yes
UKCA	No
UL	Yes
ATEX	No
DNV	Yes
KC	No
Mean Time Before Failure (MTBF)	>2,000,000 hours