

## IN700-485 Series 3000 points

Item number: IN7004853K00000

Thanks to its late configuration feature, this bidirectional gateway can be configured with Intesis MAPS to integrate: - Modbus (TCP & RTU) into BACnet (IP or MS/TP) - BACnet (IP or MS/TP) into Modbus (TCP & RTU) - BACnet (MS/TP or IP) into ASCII serial & TCP It supports the integration of up to 3000 points.



Multiprotocol Network Gateway - Up to 3000 points

### Features and benefits

- ✓ **Support for both BACnet/IP and BACnet MS/TP**  
The gateway supports both BACnet/IP and BACnet MS/TP protocols.
- ✓ **BACnet devices scan option with BACnet Explorer**  
It is possible to scan the BACnet network to discover devices using the BACnet Explorer feature.
- ✓ **Easy integration with Intesis MAPS**  
The integration process is quickly and easily managed using the Intesis MAPS configuration tool.
- ✓ **Commissioning-friendly approach with Intesis MAPS**  
Templates can be imported and reused as often as needed, significantly reducing commissioning time.
- ✓ **Configuration tool and gateway automatic updates**  
Both the Intesis MAPS configuration tool and the gateway's firmware can receive automatic updates.
- ✓ **ASCII Serial (232/485) and ASCII IP support**  
The gateway fully supports both ASCII IP and ASCII Serial (232/485).
- ✓ **ASCII bus automatic write request on value change**  
When an ASCII value changes, the gateway automatically sends a write request to the ASCII bus.
- ✓ **Personalized ASCII strings use**  
It is possible to use personalized ASCII strings on this gateway.

# IN700-485 Series 3000 points



General	
Net Width (mm)	88
Net Height (mm)	90
Net Depth (mm)	58
Net Weight (g)	194
Packed Width (mm)	127
Packed Height (mm)	86
Packed Depth (mm)	140
Packed Weight (g)	356
Operating Temperature °C Min	-10
Operating Temperature °C Max	60
Storage Temperature °C Min	-30
Storage Temperature °C Max	60
Power Consumption (W)	1.7
Input Voltage (V)	For DC: 9 .. 36 VDC, Max: 260 mA, 2.4 W For AC: 24 VAC ±10 %, 50-60 Hz, Max: 100 mA, 2.4 W Recommended voltage: 24 VDC, Max: 100 mA
Power Connector	3-pole
Configuration	Intesis MAPS
Installation Conditions	This gateway is designed to be mounted inside an enclosure. If the unit is mounted outside an enclosure, precautions should always be taken to prevent electrostatic discharge to the unit. When working inside an enclosure (e.g., making adjustments, setting switches, etc.), typical anti-static precautions should always be followed before touching the unit.
Content of Delivery	Intesis Gateway, Installation Manual, USB Configuration cable.
Not Included (in delivery)	Power supply not included.

# IN700-485 Series 3000 points



## General

Mounting	DIN rail mount (bracket included), Wall mount
Housing Materials	Plastic
Packaging Material	Cardboard
Warranty (years)	3 years

## Identification and Status

Product ID	IN7004853K00000
Country of Origin	Spain
HS Code	8517620000
Dual Usage	No
Export Control Classification Number (ECCN)	EAR99

## Physical Features

Connectors / Input / Output	Power supply, two EIA-485 ports, Ethernet, Console port USB Mini-B type, USB storage, EIA-232.
LED Indicators	Gateway and communication status.
Push Buttons	Factory reset.
DIP & Rotary Switches	EIA-485 serial port configuration.
Contains Battery	Yes
Battery Description	Manganese Dioxide Lithium button battery.

## Certifications and Standards

CE	Yes
CB	Yes
UKPSTI	Yes
UL	Yes



## Certifications and Standards

<b>KC</b>	Yes
<b>BTL</b>	Yes
<b>WEEE Category</b>	IT and telecommunications equipment

