



## Ewon Cosy+ WiFi

Item number: EC7133J\_00MA

The Ewon Cosy+ gateway establishes a secure VPN connection between the machine (PLC, HMI, or other devices) and the remote engineer. The connection happens through Talk2m, a highly secured industrial cloud service. The Ewon Cosy+ makes industrial remote access easy and secure like never before!



*Industrial VPN gateway for secure remote access to machines*

### Features and benefits

- ✓ **Successful remote connectivity in all situations**  
The Ewon Cosy+ offers multiple connectivity options for successful deployment in any situation.
- ✓ **Easily save time and money**  
Optimize costs by avoiding unnecessary service trips. Improve engineers well-being and productivity.
- ✓ **Easy - No IT skills required**  
Straightforward setup, to make machines IIoT-ready in minutes. Non-intrusive outbound connections.
- ✓ **Scalable solution that adapts to your needs**  
The Cosy+ and Talk2m offer excellent scalability - add as many devices and users as you need.
- ✓ **Maximize machine up-time and productivity**  
Industrial remote access empowers you to enhance machine uptime and boost operational efficiency.
- ✓ **State-of-the-art security**  
Built-in hardware security (Secure Element). ISO 27001 certified, machine LAN segregation, and more.
- ✓ **Efficient connectivity management**  
Manage all aspects of your connectivity from one single place (Talk2m industrial cloud service).
- ✓ **Successful worldwide connectivity**  
Benefit from Talk2m's reliable global infrastructure, with an extended Service Level Agreement.



# Ewon Cosy+ WiFi

## Data Features

<b>Router Features</b>	IP filtering, IP forwarding, NAT, Port forwarding, Proxy, Routing table, DHCP client/server
<b>VPN</b>	OpenVPN either in SSL UDP or TCP.
<b>VPN Security</b>	Communications between the remote user and the Ewon gateway are fully encrypted using the SSL/TLS protocol, thereby ensuring data authenticity, integrity & confidentiality. All users and Ewon units are authenticated using x509 SSL certificates and end-to-end traffic is encrypted using strong symmetric & asymmetric algorithms that are part of the SSL/TLS protocol cipher suite

## General

<b>Net Width (mm)</b>	42
<b>Net Height (mm)</b>	117
<b>Net Depth (mm)</b>	105
<b>Net Weight (g)</b>	217
<b>Packed Width (mm)</b>	168
<b>Packed Height (mm)</b>	45
<b>Packed Depth (mm)</b>	148
<b>Packed Weight (g)</b>	281
<b>Operating Temperature °C Min</b>	-25
<b>Operating Temperature °C Max</b>	+60
<b>Storage Temperature °C Min</b>	-30
<b>Storage Temperature °C Max</b>	+70
<b>Relative Humidity</b>	10 to 95% relative humidity (non-condensing).
<b>Input Voltage (V)</b>	12-24 VDC +/-20%, LPS
<b>Power Connector</b>	9-pole
<b>Configuration</b>	Web-Based configuration: Embedded web interface with setup wizards for configuration and maintenance (no additional software needed). Basic authentication (login/password) and session control for security.



# Ewon Cosy+ WiFi

## General

<b>Mounting</b>	DIN rail mount (bracket included), Wall mount
<b>Housing Materials</b>	Plastic
<b>Packaging Material</b>	Cardboard
<b>Warranty (years)</b>	3
<b>PLC Compatibility</b>	Rockwell Automation/Allen Bradley, Siemens, Schneider Electric, Mitsubishi Electric, Vipa, Omron, Hitachi, Keyence, Yokogawa

## Identification and Status

<b>Product ID</b>	EC7133J_00MA
<b>Model Code</b>	04002
<b>Predecessor</b>	EC6133C
<b>Country of Origin</b>	Lithuania
<b>HS Code</b>	8517699000
<b>Dual Usage</b>	No
<b>Export Control Classification Number (ECCN)</b>	5A992.c

## Physical Features

<b>Connectors / Input / Output</b>	1xDO: open drain ( MOSFET) 200mA; isolation 1.5kV, 2xDI: 2 digital inputs on the green connector of the Cosy+ devices
<b>WAN Specification</b>	up to 3 ports,10/100 Mb Ethernet.
<b>LAN Specification</b>	up to 4 ports,10/100 Mb Ethernet
<b>Contains Battery</b>	Yes

## Wireless Features

<b>Antenna Connector</b>	RP-SMA
<b>Antenna</b>	Included
<b>Frequencies &amp; Bands</b>	Channels: 1 to 11 (inclusive).



# Ewon Cosy+ WiFi

## Wireless Features

### Wireless Security

Client : WPA, WPA2 and WEP. Access Point : WPA2.

## Certifications and Standards

RoHS Compliant	Yes
CE	Yes
FCC	Yes
IC	Yes
UKCA	Yes
UL	Yes
KC	Yes
RCM	Yes
PTCRB	Yes
Environment	Temperature - Operating & Storage tested according to: IEC 60068-2-1 Cold test IEC 60068-2-2 Dry heat test IEC 60068-2-14 Change of temperature IEC 60068-2-30 Cyclic damp heat test
Vibration and Shock	Vibration & shocks tested according to: IEC 60068-2-27 Bumps IEC 60068-2-64 Vibration (broad-band random) IEC 60068-2-6 Vibration (sinusoidal)
Waste Certification (WEEE)	Yes
WEEE Category	IT and telecommunications equipment
Other Certification	Giteki T