Anybus ComBricks 1 Channel RS485 SCOPE Repeater

Item number: 101-201410C

The RS 485-IS barrier is the only available product for remotely monitoring IS segments over Ethernet from the safe zone.



Enables access to IS zones within your network remotely

Features and benefits

Meets all expectations

It complies with the specifications for PROFIBUS DP in IS segments and drives 31 RS 485-IS PROFIBUS DP devices.

Integrated oscilloscope

Anybus ProfiTrace and an Oscilloscope are integrated and also suitable for Intrinsic Safety.

Anybus ComBricks 1 Channel RS485 SCOPE Repeater



General

Net Weight (g)	187
Packed Width (mm)	6
Packed Height (mm)	14
Packed Depth (mm)	20
Packed Weight (g)	265
Operating Temperature °C Min	-20
Operating Temperature °C Max	60
Current Consumption Type Value at Vcc Nom (mA)	450 mA
Current Consumption Max value at Vcc nom (mA)	750 mA
Power Wire Diameter (mm)	< 2.5 mm²
Mounting	DIN rail mount (bracket included)
Housing Materials	Plastic
Packaging Material	Cardboard
Warranty (years)	1 Year

Identification and Status

Product ID	101-201410C
Country of Origin	Netherlands (the)
HS Code	8471800000
Dual Usage	No

Physical Features

SD Card Slot	SD

Anybus ComBricks 1 Channel RS485 SCOPE Repeater



Physical Features

Contains Battery	No

Certifications and Standards

Protection Class IP	IP20
RoHS Compliant	Yes
Product Certifications	ATEX , CE, UKCA, UL, FCC, EMC, RoHS
WEEE Category	IT and telecommunications equipment