

Ixxat CAN-IB410/PMC

Item number: 1.01.0314.22001

The Ixxat CAN-IB410/PMC is an active PMC interface card with two CAN channels and galvanic isolation. It is an easy and cost-efficient way to connect computers to a CAN bus network. Based on a modular design, the card enables simple integration into diverse industrial setups, supporting various CAN applications.



PC interface card for CAN (2 x CAN), galv. isolated

Features and benefits

- ✓ **Active CAN interface card**
Fulfills even high requirements in data pre-processing, like precise on-board time-stamping and data filtering.
- ✓ **Cost-effective connectivity**
Offers a cost-effective solution, delivering high performance at an economical price. Ideal choice for demanding applications, without having to compromise on quality.
- ✓ **PMC interface (PCI Mezzanine Card)**
Equipped with a PMC interface (PCI Mezzanine Card), the card supports high-speed data transmission, ideal for demanding industrial applications and providing fixed installation for reliable connectivity.
- ✓ **Installation of multiple cards**
Integration of multiple cards in one PC allows easy channel extension, making it suitable even for demanding settings like test benches and manufacturing plants.
- ✓ **Modular architecture for easy expansion**
Modern and modular concept enables easy extension with customer specific interfaces via expansion boards and piggyback modules.
- ✓ **Expandable LIN, high- and low-speed CAN channels**
Supports expansion boards for additional low-speed CAN, LIN, or up to four high-speed CAN channels – switchable through software.
- ✓ **Overvoltage protection**
Galvanic isolation safeguards against overvoltage and protects from potential electrical damage.
- ✓ **Comprehensive driver compatibility**
Ixxat VCI driver packages support multiple fieldbuses and allow easy switching between different PC interface types. Available as free download.
- ✓ **Powerful programming interface**
Ixxat offers versatile programming interfaces for Windows (VCI), Linux (ECI) and real-time OS (on request), enabling flexible development across multiple operating systems.
- ✓ **Analysis software included**
Ixxat canAnalyser3 Mini is included in the VCI V4 download package and enables first steps in analyzing and monitoring CAN networks.



| General | |
|---|---|
| Net Width (mm) | 74 |
| Net Height (mm) | 149 |
| Net Weight (g) | 85 |
| Packed Width (mm) | 14 |
| Packed Height (mm) | 4 |
| Packed Depth (mm) | 18 |
| Packed Weight (g) | 223 |
| Operating Temperature °C Min | -20 |
| Operating Temperature °C Max | 70 |
| Storage Temperature °C Min | -40 |
| Storage Temperature °C Max | 85 |
| Relative Humidity | 10 to 95 %, no condensation |
| Current Consumption Type Value at Vcc Nom (mA) | 650 mA (3.3 V DC) |
| Isolation | 1 kV DC for 1 sec. |
| Content of Delivery | PC interface card, user manual, available as free download: CAN driver VCI, simple CAN monitor "canAnalyser Mini" |
| Not Included (in delivery) | Comprehensive and powerful driver and software packages are available as free download |
| Mounting | PMC |
| Packaging Material | Cardboard |
| Warranty (years) | 1 |



Identification and Status

| | |
|---|-----------------|
| Product ID | 1.01.0314.22001 |
| Country of Origin | Germany |
| HS Code | 8517620000 |
| Dual Usage | No |
| Export Control Classification Number (ECCN) | EAR99 |

Physical Features

| | |
|-----------------------------|--|
| Connectors / Input / Output | 2 x D-Sub 9 connectors, 1 x PCI Mezzanine Card connector (PMC) |
| Contains Battery | No |

CAN Features

| | |
|----------------|---|
| CAN Mode | CAN high-speed (ISO 11898-2), via optional expansion: CAN low-speed (ISO 11898-3) |
| CAN Controller | CAN 2.0 A/B |
| CAN Baud Rate | CAN high-speed: 10 kBit/s to 1 Mbit/s, via optional expansion: CAN low-speed: 10 kBit/s to 125 kBit/s |

Certifications and Standards

| | |
|---------------------|-------------------------------------|
| ETIM Classification | EC000515 |
| CE | Yes |
| TELEC | No |
| WEEE Category | IT and telecommunications equipment |