



## Ewon Cosy+ Ethernet

Item number: EC71330\_00MA

The Ewon Cosy+ gateway establishes a secure VPN connection between the machine (PLC, HMI, or other devices) and the remote engineer. The connection happens through Talk2m, a highly secured industrial cloud service. The Ewon Cosy+ makes industrial remote access easy and secure like never before!



*Industrial VPN gateway for secure remote access to machines*

### Features and benefits

- ✓ **Successful remote connectivity in all situations**  
The Ewon Cosy+ offers multiple connectivity options for successful deployment in any situation.
- ✓ **Easily save time and money**  
Optimize costs by avoiding unnecessary service trips. Improve engineers well-being and productivity.
- ✓ **Easy - No IT skills required**  
Straightforward setup, to make machines IIoT-ready in minutes. Non-intrusive outbound connections.
- ✓ **Scalable solution that adapts to your needs**  
The Cosy+ and Talk2m offer excellent scalability - add as many devices and users as you need.
- ✓ **Maximize machine uptime and productivity**  
Industrial remote access empowers you to enhance machine uptime and boost operational efficiency.
- ✓ **State-of-the-art security**  
Built-in hardware security (Secure Element). ISO 27001 certified, machine LAN segregation, and more.
- ✓ **Efficient connectivity management**  
Manage all aspects of your connectivity from one single place (Talk2m industrial cloud service).
- ✓ **Successful worldwide connectivity**  
Benefit from Talk2m's reliable global infrastructure, with an extended Service Level Agreement.



# Ewon Cosy+ Ethernet

General	
Net Width (mm)	42
Net Height (mm)	117
Net Depth (mm)	99
Net Weight (g)	198
Packed Width (mm)	168
Packed Height (mm)	45
Packed Depth (mm)	148
Packed Weight (g)	261
Operating Temperature °C Min	-25
Operating Temperature °C Max	+60
Storage Temperature °C Min	-30
Storage Temperature °C Max	+70
Input Voltage (V)	12-24 VDC +/-20%, LPS
Power Connector	9-pole
Configuration	Web-Based configuration: Embedded web interface with setup wizards for configuration and maintenance (no additional software needed). Basic authentication (login/password) and session control for security.
Mounting	DIN rail mount (bracket included), Wall mount
Housing Materials	Plastic
Packaging Material	Cardboard
Warranty (years)	3



# Ewon Cosy+ Ethernet

## Data Features

<b>Router Features</b>	IP filtering, IP forwarding, NAT, Port forwarding, Proxy, Routing table, DHCP client/server
<b>VPN</b>	OpenVPN either in SSL UDP or TCP.
<b>VPN Security</b>	Communications between the remote user and the Ewon gateway are fully encrypted using the SSL/TLS protocol, thereby ensuring data authenticity, integrity & confidentiality. All users and Ewon units are authenticated using x509 SSL certificates and end-to-end traffic is encrypted using strong symmetric & asymmetric algorithms that are part of the SSL/TLS protocol cipher suite

## Identification and Status

<b>Product ID</b>	EC71330_00MA
<b>Model Code</b>	11702,01702
<b>Predecessor</b>	EC61330
<b>Country of Origin</b>	Lithuania
<b>HS Code</b>	8517620000
<b>Dual Usage</b>	No
<b>Export Control Classification Number (ECCN)</b>	5A992.c

## Physical Features

<b>Connectors / Input / Output</b>	1xDO: open drain ( MOSFET) 200mA; isolation 1.5kV, 2xDI: 2 digital inputs on the green connector of the Cosy+ devices
<b>WAN Specification</b>	up to 3 ports,10/100 Mb Ethernet.
<b>LAN Specification</b>	up to 4 ports,10/100 Mb Ethernet
<b>Contains Battery</b>	Yes

## Certifications and Standards

<b>RoHS Compliant</b>	Yes
<b>CE</b>	Yes
<b>FCC</b>	Yes
<b>IC</b>	Yes
<b>UKCA</b>	Yes



# Ewon Cosy+ Ethernet

## Certifications and Standards

<b>UL</b>	Yes
<b>UL Information</b>	The product fulfils the requirements of: EN 62368-1:2020+A11:2020, J62368-1(2023), National standard SASO-IEC 62368-1:2020, AS/NZS 62368.1:2022, CSA/UL 62368-1:2019
<b>KC</b>	Yes
<b>RCM</b>	Yes
<b>PTCRB</b>	No
<b>Environment</b>	Operating and storage temperature tested according to: IEC 60068-2-1 Cold test; IEC 60068-2-2 Dry heat test; IEC 60068-2-14. Change of temperature: IEC 60068-2-30 Cyclic damp heat test
<b>Vibration and Shock</b>	Vibration & shocks tested according to: IEC 60068-2-27 Bumps IEC 60068-2-64 Vibration (broad-band random) IEC 60068-2-6 Vibration (sinusoidal)
<b>Waste Certification (WEEE)</b>	Yes
<b>WEEE Category</b>	IT and telecommunications equipment