

## Ixxat CAN-IB200/PCle

Item number: 1.01.0233.12001

The Ixxat CAN-IB200/PCle is an active PCI Express interface card with one CAN channel and galvanic isolation. It is an easy and cost-efficient way to connect computers to a CAN bus network. Based on a modular design, the card enables simple integration into diverse industrial setups, supporting various CAN applications.



*PC interface card for CAN (1 x CAN), galv. isolated*

### Features and benefits

- ✓ **Active CAN interface card**  
Fulfills even high requirements in data pre-processing, like precise on-board time-stamping and data filtering.
- ✓ **PCle interface**  
Single-lane (1x) PCI Express interface supports high-speed data transmission, ideal for demanding industrial applications.
- ✓ **Standard slot bracket**  
Standard slot bracket size ensures compatibility with a wide range of PC systems.
- ✓ **Modular architecture for easy expansion**  
Modern and modular concept enables easy extension with customer specific interfaces via expansion boards and piggyback modules.
- ✓ **Overvoltage protection**  
Galvanic isolation safeguards against overvoltage and protects from potential electrical damage.
- ✓ **Powerful programming interface**  
Ixxat canAnalyser3 Mini is included in the VCI V4 download package and enables first steps in analyzing and monitoring CAN networks.
- ✓ **Cost-effective connectivity**  
Offers a cost-effective solution, delivering high performance at an economical price. Ideal choice for demanding applications, without having to compromise on quality.
- ✓ **Use in industrial and standard PCs**  
PC board with slot plate for fixed installation in desktop or industrial PCs, providing reliable connectivity.
- ✓ **Installation of multiple cards**  
Integration of multiple cards in one PC allows easy channel extension, making it suitable even for demanding settings like test benches and manufacturing plants.
- ✓ **Expandable LIN and low-speed CAN channel**  
Supports expansion boards for additional low-speed CAN or LIN channel – switchable through software (CAN).
- ✓ **Comprehensive driver compatibility**  
Ixxat VCI driver packages support multiple fieldbuses and allow easy switching between different PC interface types. Available as free download.
- ✓ **Analysis software included**  
Ixxat canAnalyser3 Mini is included in the VCI V4 download package and enables first steps in analyzing and monitoring CAN networks.



General	
Net Width (mm)	69
Net Height (mm)	105
Net Weight (g)	190
Packed Width (mm)	13
Packed Height (mm)	5
Packed Depth (mm)	17
Packed Weight (g)	205
Operating Temperature °C Min	0
Operating Temperature °C Max	70
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Relative Humidity	10 to 95 %, no condensation
Current Consumption Type Value at Vcc Nom (mA)	390 mA (3.3 V DC)
Current Consumption Max value at Vcc nom (mA)	550 mA (3.3 V DC)
Input Voltage (V)	3.3 V DC via PCIe socket
Power Connector	PCIe socket (3.3 V / 12 V DC)
Isolation	1 kV DC for 1 sec.
Content of Delivery	PC interface card, user manual, available as free download: CAN driver VCI, simple CAN monitor "canAnalyser Mini"
Not Included (in delivery)	Comprehensive and powerful driver and software packages are available as free download



## General

Mounting	PCI Express
Packaging Material	Cardboard
Warranty (years)	1

## Identification and Status

Product ID	1.01.0233.12001
Country of Origin	Germany
HS Code	8517620000
Dual Usage	No
Export Control Classification Number (ECCN)	EAR99

## Physical Features

Connectors / Input / Output	1 x D-Sub 9 connector, 1 x PCI express (V1.1), single lane port (x1)
Contains Battery	No

## CAN Features

CAN Mode	CAN high-speed (ISO 11898-2), via optional expansion: CAN low-speed (ISO 11898-3)
CAN Transceiver	TI SN65HVD251
CAN Controller	CAN 2.0 A/B
CAN Baud Rate	CAN high-speed: 10 kBit/s to 1 Mbit/s, via optional expansion: CAN low-speed: 10 kBit/s to 125 kBit/s

## LIN Features

LIN Mode	via optional expansion: LIN (ISO 9141), LIN VBAT 8-48 V DC for product version 3.0 and newer, LIN VBAT 8-18 V DC for product version 2.0 and older
LIN Baud Rate	via optional expansion: 10 kBit/s to 25 kBit/s

## Certifications and Standards

ETIM Classification	EC000515
CE	Yes
FCC	Yes



## Certifications and Standards

TELEC	No
WEEE Category	IT and telecommunications equipment