



DA Series FlexEdge Module, Dual PID, SSR Output and Heater Current Monitor

Item number: DAM00PDP2SM00000

The FlexEdge 2PID with SSR Outputs Module easily upgrades, adapts and expands almost any industrial application with a field-installable module. Rugged packaging built for long life and superior performance in harsh conditions. Dual loop PID control with 4 solid state relay outputs + optional heat current monitor input.



Enhance your DA70 controller with true modular PID control for multi-zone control applications.

Features and benefits

- ✓ **Field-installable I/O for your DA74**
Do more with your DA70. Plugs easily into your FlexEdge for additional input and output capability. Auto-addressing minimizes configuration time.
- ✓ **Universal inputs**
Accept TC, RTD, 0-10 V and 0/4-20 mA signals
- ✓ **Solid State Relay (SSR) outputs**
Outputs 1, 2, 3 and 4 available as Solid State NFET relay.
- ✓ **Easy to use graphical interface**
Configured with Crimson® configuration software (version 3.2 or later). User-friendly web browser interface make it easy to set up new systems and recalibrate.
- ✓ **LED status monitoring**
One status LED shows module condition. Output LEDs indicate status of outputs. Alarm LEDs are lit during an internal alarm condition.
- ✓ **Leading industry certifications**
ATEX/IECEx and Class 1, Division 2 approvals for hazardous locations. ABS type approval for shipboard applications. CE approved and RoHS compliant.
- ✓ **Dual PID control**
Perform virtually any combination of time proportioning for heat, cool, or heat/cool applications. PID control with overshoot suppression that allows the quickest response without excessive overshoot.
- ✓ **Optional Heater Current Monitor Input**
Useful for early warning of heater degradation or heater circuit failure instead of waiting for high/low temperature shutdown alarm. Connects to external current transformer with output of 100 mA AC.
- ✓ **Flexible operation**
Module can operate in On/Off, P, PI, or PID control mode, and use an on-demand Auto-Tune that establishes the tuning constants. The PID constants may be fine-tuned through the serial or Ethernet interface.
- ✓ **Simple to set up and deploy**
Pluggable wire clamp screw block terminals are provided for the I/O wiring connections. Comes with an on-device wiring diagram.
- ✓ **Designed for harsh industrial environments**
Engineered to deliver uncompromising performance in demanding environments. IP30 enclosure. Operating temperature of -40 °C to 75 °C.
- ✓ **Power supplied by FlexEdge DA70 host controller**
Maximum power is 2.7 W. Hot-swappable in non-hazardous locations.

DA Series FlexEdge Module, Dual PID, SSR Output and Heater Current Monitor



General	
Net Weight (g)	0.01
Packed Width (mm)	215.9
Packed Height (mm)	127
Packed Depth (mm)	215.9
Packed Weight (g)	0.01
Operating Temperature °C Min	-40
Operating Temperature °C Max	75
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Relative Humidity	0 to 85% max. Relative humidity, non-condensing
Power Consumption (W)	2
Maximum Installation Altitude (m)	2000
Mounting	DIN rail mount (bracket included)
Housing Materials	Metal Housing, Plastic
Packaging Material	Cardboard
Warranty (years)	3
Identification and Status	
Product ID	DAM00PDP2SM00000
Country of Origin	United States of America (the)
HS Code	8517790000

DA Series FlexEdge Module, Dual PID, SSR Output and Heater Current Monitor



Identification and Status

Dual Usage	No
Export Control Classification Number (ECCN)	EAR99

Physical Features

Connectors / Input / Output	plug-in jacks
SD Card Slot	Yes
Flash Drive	No
Contains Battery	No

Certifications and Standards

Protection Class IP	IP30
RoHS Compliant	Yes
CE	Yes
FCC	No
UKCA	Yes
UL	Yes
ATEX	Yes
DNV	No
KC	No
Vibration and Shock	Shock: IEC 68-2-27: Operational 40 g